

SAFETY DATA SHEET

Section 1. Identification

Product identifier : UP0830
Product name : POWERCAN ETCH PRIMER AEROSOL
Date of issue : 2/19/2026
Version : 1

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Coating component.
Uses advised against : Not for sale to or use by consumers.

Supplier's details : U-POL CANADA LIMITED
 P.O. BOX 48600
 VANCOUVER, BC V7X 1T2
 1-800-424-9300
 technicalsupport@u-pol.com

Product information : (855) 6-AXALTA

Emergency telephone number : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

Section 2. Hazard identification

Classification of the substance or mixture : AEROSOLS - Category 1
 SKIN IRRITATION - Category 2
 SERIOUS EYE DAMAGE - Category 1
 CARCINOGENICITY - Category 2
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222, H229 - Extremely flammable aerosol. Pressurized container: may burst if heated.
 H315 - Causes skin irritation.
 H318 - Causes serious eye damage.
 H336 - May cause drowsiness or dizziness.
 H351 - Suspected of causing cancer.
 H370 - Causes damage to organs.

Precautionary statements

Section 2. Hazard identification

Prevention	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P271 - Use only outdoors or in a well-ventilated area. P260 - Do not breathe dust or mist. P270 - Do not eat, drink or smoke when using this product. P264 - Wash hands thoroughly after handling. P251 - Do not pierce or burn, even after use. P280 - Wear protective gloves, protective clothing and eye or face protection.
Response	: P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor. P304 + P340, P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P332 + P313 - If skin irritation occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: P405 - Store locked up. P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

Ingredient name	Synonyms	% (w/w)	Identifiers
dimethyl ether	Methane, 1,1'-oxybis-; Methane, oxybis-; Methyl ether; methoxymethane; propane—methoxymethane (95%/5%); isobutane—methoxymethane (12%/88%); 1,1-difluoroethane—methoxymethane; 1,1-difluoroethane—methoxymethane— isobutane; isobutane—methoxymethane; dimethyl ether; RE 170; dimethyl oxide; R511a; R290—RE170 (95%/5%)	≥30 - ≤60	CAS: 115-10-6
methyl acetate	Acetic acid, methyl ester; Methyl ester of acetic acid; Methyl	≥7 - ≤13	CAS: 79-20-9

Section 3. Composition/information on ingredients

acetone	ethanoate; Acetic acid methyl ester; ACETATE, METHYL; Acetic methylester propan-2-one; propanone; 2-Propanone; Ketone propane; Dimethyl ketone; β -ketonepropane; acetone; dimethylketone; methyl ketone; propanone; pyroacetic acid; pyroacetic ether; dimethylformaldehyde; methyl ketone; Acetone (I); 2-Propanone (I); DIMETHYLFORMALDEHYDE; 2-OXOPROPANE	$\geq 7 - \leq 13$	CAS: 67-64-1
1-methoxy-2-propanol	monopropylene glycol methyl ether; 1-methoxypropan-2-ol; 2-Propanol, 1-methoxy-; Propylene glycol monomethyl ether; Dowtherm 209; Propylene glycol methyl ether; 1-Methoxy-2-hydroxypropane; 2-Methoxy-1-methylethanol; PGME; methoxyisopropanol; α -propylene glycol 1-methyl ether	$\geq 5 - \leq 10$	CAS: 107-98-2
Normal butyl alcohol	n-butanol; 1-Butanol; n-BUTYL ALCOHOL; n-Propyl carbinol; 1-Hydroxybutane; Butyl alcohol; mixture, containing by weight: - 30 % or more, but not more than 40 % of a copolymer of vinyl methyl ether and monobutyl maleate, - 10 % or more, but not more than 20 % of a copolymer of vinyl methyl ether and monoethyl maleate, - 40 % or more, but not more than 55 % of ethanol, - 1 % or more, but not more than 7 % of 1-butanol; 1-Butanol (I); n-Butyl alcohol (I); METHYLOLPROPANE; Butyl hydroxide	$\geq 5 - \leq 10$	CAS: 71-36-3
XYLENE	Benzene, dimethyl-; Xylol; Benzene, dimethyl-, mixed isomers; xylene, mixed isomers, pure; xylene, crude; photosensitive emulsion consisting of cyclized polyisoprene containing: — 55 % or more but not more than 75 % by weight of xylene (CAS RN 1330-20-7) and — 12 % or more but not more than 18 % by weight of ethylbenzene (CAS RN 100-41-4); Benzene, dimethyl-; Xylene (mixed); xylene (total); Xylenes; Dimethylbenzene	$\geq 0.5 - \leq 1.5$	CAS: 1330-20-7
2-methylpropan-1-ol	iso-butanol; 1-Propanol, 2-methyl-; Isobutyl alcohol; Isobutanol; 2-Methyl-1-propanol; Isopropylcarbinol; IBA; i-	$\geq 0.5 - \leq 1.5$	CAS: 78-83-1

Section 3. Composition/information on ingredients

carbon black, non respirable	Butyl alcohol; catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol; isobutanol; iso-butanol; Isobutyl alcohol (I,T)	≥0.5 - ≤1.5	CAS: 1333-86-4
titanium dioxide	Lampblack; Acetylene black; C.I. 77266; C.I. Pigment Black 6; C.I. Pigment Black 7; Charcoal	≥0.1 - ≤1	CAS: 13463-67-7
ethylbenzene	Titanium oxide; Titanium oxide (TiO ₂); Titanium peroxide; Rutile; C.I. Pigment White 6	≥0.1 - ≤1	CAS: 100-41-4
	Benzene, ethyl-; Phenylethane; Ethylbenzol; photosensitive emulsion consisting of cyclized polyisoprene containing: — 55 % or more but not more than 75 % by weight of xylene (CAS RN 1330-20-7) and — 12 % or more but not more than 18 % by weight of ethylbenzene (CAS RN 100-41-4); EB; Mono-(or di-) methyl (ethyl,bromoallyl, bromopropyl,oxycarbonyl orchloropropyl,oxycarbonyl) benzene		

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Section 4. First-aid measures

- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Causes damage to organs following a single exposure if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes damage to organs following a single exposure in contact with skin. Causes skin irritation.
- Ingestion** : Causes damage to organs following a single exposure if swallowed. Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

Section 4. First-aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
phosphorus oxides
metal oxide/oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Section 6. Accidental release measures

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
- Storage code** : IB

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
<p>dimethyl ether</p> <p>methyl acetate</p>	<p>CA British Columbia Provincial (Canada, 9/2024) TWA 8 hours: 1000 ppm.</p> <p>CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 250 ppm. TWA 8 hours: 200 ppm.</p> <p>CA British Columbia Provincial (Canada, 9/2024) TWA 8 hours: 200 ppm. STEL 15 minutes: 250 ppm.</p> <p>CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 200 ppm. STEL 15 minutes: 250 ppm.</p> <p>CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 200 ppm. TWAEV 8 hours: 606 mg/m³. STEV 15 minutes: 250 ppm. STEV 15 minutes: 757 mg/m³.</p> <p>CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 606 mg/m³. OEL 15 minutes: 757 mg/m³. OEL 15 minutes: 250 ppm. OEL 8 hours: 200 ppm.</p>
<p>acetone</p>	<p>CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 750 ppm. TWA 8 hours: 500 ppm.</p> <p>CA British Columbia Provincial (Canada, 9/2024) TWA 8 hours: 250 ppm. STEL 15 minutes: 500 ppm.</p> <p>CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 250 ppm. STEL 15 minutes: 500 ppm.</p> <p>CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 250 ppm. STEV 15 minutes: 500 ppm.</p> <p>CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 1200 mg/m³. OEL 15 minutes: 1800 mg/m³. OEL 8 hours: 500 ppm. OEL 15 minutes: 750 ppm.</p>
<p>1-methoxy-2-propanol</p>	<p>CA Saskatchewan Provincial (Canada, 4/2021) STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm.</p> <p>CA British Columbia Provincial (Canada, 9/2024) STEL 15 minutes: 100 ppm. TWA 8 hours: 50 ppm.</p> <p>CA Ontario Provincial (Canada, 6/2019) TWA 8 hours: 50 ppm.</p>

Section 8. Exposure controls/personal protection

Normal butyl alcohol

STEL 15 minutes: 100 ppm.

CA Quebec Provincial (Canada, 2/2024)

TWAEV 8 hours: 50 ppm.

STEV 15 minutes: 100 ppm.

CA Alberta Provincial (Canada, 3/2023)

OEL 8 hours: 100 ppm.

OEL 15 minutes: 553 mg/m³.

OEL 8 hours: 369 mg/m³.

OEL 15 minutes: 150 ppm.

CA Saskatchewan Provincial (Canada, 4/2021)

STEL 15 minutes: 30 ppm.

TWA 8 hours: 20 ppm.

CA British Columbia Provincial (Canada, 9/2024)

TWA 8 hours: 15 ppm.

C: 30 ppm.

CA Ontario Provincial (Canada, 6/2019)

TWA 8 hours: 20 ppm.

CA Quebec Provincial (Canada, 2/2024)

TWAEV 8 hours: 20 ppm.

CA Alberta Provincial (Canada, 3/2023)

OEL 8 hours: 60 mg/m³.

OEL 8 hours: 20 ppm.

XYLENE

CA Saskatchewan Provincial (Canada, 4/2021) [Xylene]

STEL 15 minutes: 150 ppm.

TWA 8 hours: 100 ppm.

CA British Columbia Provincial (Canada, 9/2024) [xylene (o, m & p isomers)]

TWA 8 hours: 100 ppm.

STEL 15 minutes: 150 ppm.

CA Ontario Provincial (Canada, 6/2019) [Xylene (o-, m-, p-isomers)]

STEL 15 minutes: 150 ppm.

TWA 8 hours: 100 ppm.

CA Quebec Provincial (Canada, 2/2024) [Xylene]

TWAEV 8 hours: 100 ppm.

TWAEV 8 hours: 434 mg/m³.

STEV 15 minutes: 150 ppm.

STEV 15 minutes: 651 mg/m³.

CA Alberta Provincial (Canada, 3/2023) [Dimethylbenzene]

OEL 8 hours: 100 ppm.

OEL 15 minutes: 651 mg/m³.

OEL 15 minutes: 150 ppm.

OEL 8 hours: 434 mg/m³.

2-methylpropan-1-ol

CA Saskatchewan Provincial (Canada, 4/2021)

STEL 15 minutes: 60 ppm.

TWA 8 hours: 50 ppm.

CA British Columbia Provincial (Canada, 9/2024)

TWA 8 hours: 50 ppm.

Section 8. Exposure controls/personal protection

carbon black, non respirable

CA Ontario Provincial (Canada, 6/2019)
TWA 8 hours: 50 ppm.

CA Quebec Provincial (Canada, 2/2024)
TWAEV 8 hours: 50 ppm.
TWAEV 8 hours: 152 mg/m³.

CA Alberta Provincial (Canada, 3/2023)
OEL 8 hours: 50 ppm.
OEL 8 hours: 152 mg/m³.

CA Saskatchewan Provincial (Canada, 4/2021)

STEL 15 minutes: 7 mg/m³.
TWA 8 hours: 3.5 mg/m³.

CA British Columbia Provincial (Canada, 9/2024) Carc 2B.

TWA 8 hours: 3 mg/m³. Form: Inhalable.

CA Ontario Provincial (Canada, 6/2019)
TWA 8 hours: 3 mg/m³. Form: Inhalable particulate matter..

CA Quebec Provincial (Canada, 2/2024)
C3.

TWAEV 8 hours: 3 mg/m³. Form: inhalable aerosol fraction.

CA Alberta Provincial (Canada, 3/2023)
OEL 8 hours: 3.5 mg/m³.

titanium dioxide

CA Saskatchewan Provincial (Canada, 4/2021)

STEL 15 minutes: 20 mg/m³.
TWA 8 hours: 10 mg/m³.

CA British Columbia Provincial (Canada, 9/2024) Carc 2B.

TWA 8 hours: 10 mg/m³. Notes: The 8-hour TWA listed in the Table is for the total dust. The substance also has an 8-hour TWA of 3 mg/m³ for the respirable fraction.

CA Ontario Provincial (Canada, 6/2019)
TWA 8 hours: 10 mg/m³.

CA Quebec Provincial (Canada, 2/2024)
TWAEV 8 hours: 10 mg/m³. Form: total particulate matter.

CA Alberta Provincial (Canada, 3/2023)
OEL 8 hours: 10 mg/m³.

ethylbenzene

CA Saskatchewan Provincial (Canada, 4/2021)

STEL 15 minutes: 125 ppm.
TWA 8 hours: 100 ppm.

CA British Columbia Provincial (Canada, 9/2024) Carc 2B.

TWA 8 hours: 20 ppm.

CA Ontario Provincial (Canada, 6/2019)
TWA 8 hours: 20 ppm.

CA Quebec Provincial (Canada, 2/2024)
C3.

TWAEV 8 hours: 20 ppm.

CA Alberta Provincial (Canada, 3/2023)
OEL 8 hours: 100 ppm.

Section 8. Exposure controls/personal protection

OEL 8 hours: 434 mg/m³.
 OEL 15 minutes: 543 mg/m³.
 OEL 15 minutes: 125 ppm.

Biological exposure indices

No exposure indices known.

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Liquid.
Color	: Gray.
Odor	: Characteristic.
Odor threshold	: Not available.
pH	: Not applicable.
Melting point/freezing point	: Technically not possible to measure
Boiling point or initial boiling point and boiling range	: Not applicable.
Flash point	: Closed cup: -41°C (-41.8°F)
Evaporation rate	: Not available.
Flammability	: Not available.
Lower and upper explosion limit/flammability limit	: Lower: 1.4% Upper: 26.2%
Vapor pressure	: 251.7 kPa (1887.7 mm Hg)
Relative vapor density	: Not available.
Relative density	: Not available.
Density	: 0.8 g/cm ³
Solubility in water	: Not available.
Miscible with water	: Yes.
Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	: 270°C (518°F)
Decomposition temperature	: Not applicable.
Heat of combustion	: 26.22 kJ/g
Viscosity	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): Not available.

Particle characteristics

Median particle size : Not applicable.

Aerosol product

Type of aerosol : Spray

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

dimethyl ether

Result

Rat - Oral - LD50

>99999 mg/kg

Rat - Dermal - LD50

>99999 mg/kg

Rat - Inhalation - LC50 Vapor

309 g/m³ [4 hours]

Rat - Inhalation - LC50 Gas.

164000 ppm [4 hours]

Toxic effects: Behavioral - Ataxia Behavioral - Coma

methyl acetate

Rat - Oral - LD50

>5 g/kg

Rabbit - Dermal - LD50

>5 g/kg

acetone

Rat - Oral - LD50

5800 mg/kg

Toxic effects: Behavioral - Altered sleep time (including change in righting reflex) Behavioral - Tremor

Rabbit - Dermal - LD50

2001 mg/kg

Rat - Inhalation - LC50 Vapor

21 mg/l [4 hours]

1-methoxy-2-propanol

Rabbit - Dermal - LD50

13 g/kg

Rat - Oral - LD50

6600 mg/kg

Toxic effects: Brain and Coverings - Other degenerative changes Behavioral - General anesthetic Lung, Thorax, or Respiration - Dyspnea

Normal butyl alcohol

Rat - Oral - LD50

790 mg/kg

Toxic effects: Liver - Fatty liver degeneration Kidney, Ureter, and Bladder - Other changes Blood - Other changes

Rabbit - Dermal - LD50

3400 mg/kg

Rat - Inhalation - LC50 Vapor

24000 mg/m³ [4 hours]

XYLENE

Rat - Oral - LD50

4300 mg/kg

Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder - Other changes

Rat - Inhalation - LC50 Gas.

5000 ppm [4 hours]

2-methylpropan-1-ol

Rat - Oral - LD50

2460 mg/kg

Rabbit - Dermal - LD50

3400 mg/kg

carbon black, non respirable

Rat - Oral - LD50

>15400 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity)

Section 11. Toxicological information

ethylbenzene

Rat - Oral - LD50

3500 mg/kg

Toxic effects: Liver - Other changes
Kidney, Ureter, and Bladder - Other changes

Rabbit - Dermal - LD50

>5000 mg/kg

Conclusion/Summary [Product] : Not available.

Skin corrosion/irritation**Product/ingredient name**

methyl acetate

Result**Rabbit - Skin - Mild irritant**Duration of treatment/exposure: 24 hoursAmount/concentration applied: 500 mg**Rabbit - Skin - Moderate irritant**Duration of treatment/exposure: 24 hoursAmount/concentration applied: 20 mg

acetone

Rabbit - Skin - Mild irritantDuration of treatment/exposure: 24 hoursAmount/concentration applied: 500 mg

1-methoxy-2-propanol

Rabbit - Skin - Mild irritantAmount/concentration applied: 395 mg

Normal butyl alcohol

Rabbit - Skin - Mild irritantAmount/concentration applied: 500 mg**Rabbit - Skin - Moderate irritant**Duration of treatment/exposure: 24 hoursAmount/concentration applied: 20 mg

XYLENE

Rat - Skin - Mild irritantDuration of treatment/exposure: 8 hoursAmount/concentration applied: 60 uL**Rabbit - Skin - Moderate irritant**Duration of treatment/exposure: 24 hoursAmount/concentration applied: 500 mg**Rabbit - Skin - Moderate irritant**Amount/concentration applied: 100 %

ethylbenzene

Rabbit - Skin - Mild irritantDuration of treatment/exposure: 24 hoursAmount/concentration applied: 15 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation**Product/ingredient name**

methyl acetate

Result**Rabbit - Eyes - Moderate irritant**Duration of treatment/exposure: 24 hoursAmount/concentration applied: 100 mg

acetone

Human - Eyes - Mild irritantAmount/concentration applied: 186300 ppm**Rabbit - Eyes - Mild irritant**Amount/concentration applied: 10 uL**Rabbit - Eyes - Moderate irritant**Duration of treatment/exposure: 24 hours

Section 11. Toxicological information

Normal butyl alcohol

Amount/concentration applied: 20 mg
Rabbit - Eyes - Severe irritant
Amount/concentration applied: 20 mg
Rabbit - Eyes - Severe irritant
Duration of treatment/exposure: 24 hours
Amount/concentration applied: 2 mg
Rabbit - Eyes - Severe irritant
Amount/concentration applied: 0.005 MI
Rabbit - Eyes - Severe irritant
Amount/concentration applied: 1.62 mg
Rabbit - Eyes - Cornea opacity
 OECD [Acute Eye Irritation/Corrosion]
Observation period: 7 days
Irritation score: 2.11
 Not reversible

XYLENE

Rabbit - Eyes - Mild irritant
Amount/concentration applied: 87 mg
Rabbit - Eyes - Severe irritant
Duration of treatment/exposure: 24 hours
Amount/concentration applied: 5 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Classification

Section 11. Toxicological information

Product/ingredient name	IARC	NTP	ACGIH
acetone	-	-	A4
1-methoxy-2-propanol	-	-	A4
XYLENE	3	-	A4
carbon black, non respirable	2B	-	A3
titanium dioxide	2B	-	A3
ethylbenzene	2B	-	A3

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
methyl acetate	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
acetone	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
1-methoxy-2-propanol	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
Normal butyl alcohol	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
XYLENE	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
2-methylpropan-1-ol	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
ethylbenzene	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

Aspiration hazard

Product/ingredient name	Result
XYLENE	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Section 11. Toxicological information

- Inhalation** : Causes damage to organs following a single exposure if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes damage to organs following a single exposure in contact with skin. Causes skin irritation.
- Ingestion** : Causes damage to organs following a single exposure if swallowed. Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

- General** : No known significant effects or critical hazards.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

Numerical measures of toxicity

Section 11. Toxicological information

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PC ETCH DARK GREY AEROSOL (OALACDDG)	10268.0	11690.4	399241.2	N/A	N/A
dimethyl ether	N/A	N/A	164000	309	N/A
acetone	5800	2001	N/A	21	N/A
1-methoxy-2-propanol	6600	13000	N/A	N/A	N/A
Normal butyl alcohol	790	3400	N/A	24	N/A
XYLENE	4300	1100	5000	N/A	N/A
2-methylpropan-1-ol	2460	3400	N/A	N/A	N/A
ethylbenzene	3500	N/A	N/A	11	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name

methyl acetate

Result

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 28 to 32 days; Size: 17.5 mm; Weight: 0.087 g
320 mg/l [96 hours]

Effect: Mortality

acetone

Acute - LC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*

10 mg/l [48 hours]

Effect: Mortality

Chronic - NOEC - Marine water

Algae - Green algae - *Ulva pertusa*

4.95 mg/l [96 hours]

Effect: Reproduction

Acute - EC50 - Marine water

Algae - Green algae - *Ulva pertusa*

20.565 mg/l [96 hours]

Effect: Reproduction

Chronic - NOEC - Fresh water

Crustaceans - Daphnia - *Daphniidae*

0.016 ml/l [21 days]

Effect: Population

Acute - LC50 - Fresh water

Fish - Guppy - *Poecilia reticulata*

Age: 4 to 12 months; Size: 2 to 10 cm; Weight: 0.5 to 14 g
5600 ppm [96 hours]

Effect: Mortality

1-methoxy-2-propanol

Acute - LC50

OECD 203

Fish - Trout

≥1000 mg/l [96 hours]

Acute - LC50

OECD 202

Section 12. Ecological information

Normal butyl alcohol	<p>Daphnia - Daphnia >21100 mg/l [48 hours] Acute - LC50 - Fresh water Fish - Fathead minnow - <i>Pimephales promelas</i> <u>Age</u>: 33 days; <u>Size</u>: 20.6 mm; <u>Weight</u>: 0.119 g 1730 mg/l [96 hours] <u>Effect</u>: Mortality Acute - EC50 - Fresh water Daphnia - Water flea - <i>Daphnia magna</i> <u>Age</u>: 6 to 24 hours 1983 mg/l [48 hours] <u>Effect</u>: Intoxication</p>
XYLENE	<p>Acute - LC50 - Fresh water Fish - Fathead minnow - <i>Pimephales promelas</i> <u>Age</u>: 31 days; <u>Size</u>: 18.4 mm; <u>Weight</u>: 0.077 g 13.4 mg/l [96 hours] <u>Effect</u>: Mortality EC50 Crustaceans - <i>Penaeus monodon</i> 3.82 mg/l [48 hours]</p>
2-methylpropan-1-ol	<p>Acute - LC50 - Fresh water Fish - Rainbow trout,donaldson trout - <i>Oncorhynchus mykiss</i> <u>Weight</u>: 1.67 g 1330 mg/l [96 hours] <u>Effect</u>: Mortality Acute - LC50 - Marine water Crustaceans - Brine shrimp - <i>Artemia salina</i> 600 mg/l [48 hours] <u>Effect</u>: Mortality Chronic - NOEC - Fresh water Daphnia - Water flea - <i>Daphnia magna</i> <u>Age</u>: ≤24 hours 4 mg/l [21 days] <u>Effect</u>: Reproduction</p>
titanium dioxide	<p>Acute - LC50 - Marine water Fish - Mummichog - <i>Fundulus heteroclitus</i> >1000 mg/l [96 hours] <u>Effect</u>: Mortality</p>
ethylbenzene	<p>Acute - LC50 - Marine water Crustaceans - Brine shrimp - <i>Artemia sp.</i> - Nauplii <u>Age</u>: 2 to 3 13.3 mg/l [48 hours] <u>Effect</u>: Mortality Acute - EC50 - Fresh water Algae - Green algae - <i>Raphidocelis subcapitata</i> 3600 µg/l [96 hours] <u>Effect</u>: Population</p>

Conclusion/Summary [Product] : Not available.

Persistence and degradability

Product/ingredient name	Result
--------------------------------	---------------

Section 12. Ecological information

1-methoxy-2-propanol	OECD 301E 96% [28 days]
XYLENE	OECD 301 F 90% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1-methoxy-2-propanol	-	-	Readily
XYLENE	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
dimethyl ether	0.07	-	Low
methyl acetate	0.18	-	Low
acetone	-0.23	-	Low
1-methoxy-2-propanol	<1	-	Low
Normal butyl alcohol	1	-	Low
XYLENE	3.12	8.1 to 25.9	Low
2-methylpropan-1-ol	1	-	Low
ethylbenzene	3.6	-	Low

Mobility in soil

Soil/Water partition coefficient : Not available.

Other adverse effects





No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

Section 14. Transport information

	TDG Classification	DOT Classification	IMDG	IATA
UN number	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	Aerosols, flammable
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

Additional information

TDG Classification : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).

DOT Classification : **Reportable quantity** 7984.8 lbs / 3625.1 kg [1197.1 gal / 4531.4 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

Section 15. Regulatory information

Canadian lists

Canadian NPRI : The following components are listed: dimethylether; other glycol ethers and acetates (and their isomers); n-butyl alcohol; zinc (and its compounds); xylene (all isomers); i-butyl alcohol

CEPA Toxic substances : None of the components are listed.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Section 15. Regulatory information

Not listed.

Inventory list

- Canada** : At least one component is not listed.
United States : All components are listed or exempted.

Section 16. Other information

History

- Date of issue** : 2/19/2026
Version : 1
Product stewardship and regulatory compliance.

- Key to abbreviations** : ATE = Acute Toxicity Estimate
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations
HPR = Hazardous Products Regulations

🔍 Indicates information that has changed from previously issued version.

Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2026 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.