
SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product identifier : S2081EV
Product name : SYSTEM 20 DIAMOND UHS CLEARCOAT (3:1)
Product type : Liquid.
Other means of identification : S2081EV/1; S2081EV/5
Date of issue/ Date of revision : 19 February 2026
Version : 1
Date of previous issue : No previous validation

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Coating component.
Uses advised against : Not for sale to or use by consumers.

1.3 Details of the supplier of the safety data sheet

U-POL NETHERLANDS B.V,
DE GEER 14,
4004LT TIEL,
NETHERLANDS
+31 20 240 2216
sds-competence@axalta.com

e-mail address of person responsible for this SDS : sds-competence@axalta.com

National contact

U-POL LTD,
DENINGTON ROAD,
WELLINGBOROUGH,
NN8 2QH
+44 (0) 1933 230310
sds-competence@axalta.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : 010-456 6700 (9:00-17:00);112

Supplier

+(44)-870-8200418

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225

Skin Sens. 1, H317

Carc. 2, H351

STOT SE 3, H336

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Contains : n-butyl acetate
4-methylpentan-2-one
2-hydroxyethyl methacrylate
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)
propionyl- ω -hydroxypoly(oxyethylene) and α -3
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl
1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Hazard statements : H225 - Highly flammable liquid and vapour.
H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.
H351 - Suspected of causing cancer.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P201 - Obtain special instructions before use.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.
P261 - Avoid breathing vapour.

Response : P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
P302 + P352 - IF ON SKIN: Wash with plenty of water.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label elements : EUH066 - Repeated exposure may cause skin dryness or cracking.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

SECTION 2: Hazards identification

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4	≥10 - ≤25	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
4-methylpentan-2-one	REACH #: 01-2119473980-30 EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	<10	Flam. Liq. 2, H225 Acute Tox. 4, H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336 EUH066	ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
Hydrocarbons, C9, aromatics	REACH #: 01-2119455851-35 EC: 918-668-5	<10	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	-	[1]
heptan-2-one	REACH #: 01-2119902391-49 EC: 203-767-1 CAS: 110-43-0	≤10	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H332 STOT SE 3, H336	ATE [Oral] = 1600 mg/kg ATE [Inhalation (vapours)] = 16.8 mg/l	[1] [2]
2-butoxyethyl acetate	REACH #: 01-2119475112-47 EC: 203-933-3 CAS: 112-07-2 Index: 607-038-00-2	≤3	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332	ATE [Oral] = 1880 mg/kg ATE [Dermal] = 1500 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
2-hydroxyethyl methacrylate	REACH #: 01-2119490169-29 EC: 212-782-2 CAS: 868-77-9 Index: 607-124-00-X	<1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-	REACH #: 01-0000015075-76	<1	Skin Sens. 1A, H317 Aquatic Chronic 2,	-	[1]

SECTION 3: Composition/information on ingredients

butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly (oxyethylene) and α -3	EC: 400-830-7		H411		
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≤ 0.3	Skin Sens. 1A, H317 Repr. 2, H361f (oral) Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	M [Acute] = 1 M [Chronic] = 1	[1]

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

SECTION 4: First aid measures

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-hydroxyethyl methacrylate, reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly(oxyethylene) and α -3, Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Recommended: alcohol-resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

SECTION 6: Accidental release measures

6.3 Methods and material for containment and cleaning up : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling : Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

Information on fire and explosion protection
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

7.3 Specific end use(s)

SECTION 7: Handling and storage

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Identifiers	Exposure limit values
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4	Work environment authority Regulation 2018:1 (Sweden, 11/2022) [butyl acetate] TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m ³ . STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ . EU OEL (Europe, 1/2022) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ . TWA 8 hours: 241 mg/m ³ . TWA 8 hours: 50 ppm.
4-methylpentan-2-one	REACH #: 01-2119473980-30 EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	Work environment authority Regulation 2018:1 (Sweden, 11/2022) TWA 8 hours: 20 ppm. TWA 8 hours: 83 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 200 mg/m ³ . EU OEL (Europe, 1/2022) TWA 8 hours: 20 ppm. TWA 8 hours: 83 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 208 mg/m ³ .
heptan-2-one	REACH #: 01-2119902391-49 EC: 203-767-1 CAS: 110-43-0	Work environment authority Regulation 2018:1 (Sweden, 11/2022) TWA 8 hours: 25 ppm. TWA 8 hours: 120 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 475 mg/m ³ . EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 238 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 475 mg/m ³ .
2-butoxyethyl acetate	REACH #: 01-2119475112-47 EC: 203-933-3 CAS: 112-07-2 Index: 607-038-00-2	Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. TWA 8 hours: 10 ppm. TWA 8 hours: 70 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 333 mg/m ³ . EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 133 mg/m ³ .

SECTION 8: Exposure controls/personal protection

		STEL 15 minutes: 50 ppm. STEL 15 minutes: 333 mg/m ³ .
--	--	--

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

n-butyl acetate

Result

DNEL - Workers - Short term - Dermal

11 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Oral

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Oral

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

3.4 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

6 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Dermal

11 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

12 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

35.7 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

300 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

300 mg/m³

SECTION 8: Exposure controls/personal protection

Effects: Systemic

DNEL - Workers - Long term - Inhalation

300 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

600 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

600 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

300 mg/m³

Effects: Systemic

4-methylpentan-2-one

DNEL - Workers - Long term - Dermal

11.8 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

83 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

83 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

208 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

208 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

4.2 mg/kg bw/day

Effects: Systemic

Hydrocarbons, C9, aromatics

DNEL - Workers - Long term - Inhalation

151 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

12.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

32 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

7.5 mg/kg bw/day

Effects: Systemic

SECTION 8: Exposure controls/personal protection

heptan-2-one	<p>DNEL - General population - Long term - Oral 7.5 mg/kg bw/day <u>Effects:</u> Systemic</p> <p>DNEL - Workers - Long term - Inhalation 83.2 ppm <u>Effects:</u> Systemic</p>
	<p>DNEL - General population - Long term - Oral 23.32 mg/kg bw/day <u>Effects:</u> Systemic</p> <p>DNEL - General population - Long term - Dermal 23.32 mg/kg bw/day <u>Effects:</u> Systemic</p>
	<p>DNEL - Workers - Long term - Dermal 54.27 mg/kg bw/day <u>Effects:</u> Systemic</p> <p>DNEL - General population - Long term - Inhalation 84.31 mg/m³ <u>Effects:</u> Systemic</p>
	<p>DNEL - Workers - Long term - Inhalation 394.25 mg/m³ <u>Effects:</u> Systemic</p> <p>DNEL - Workers - Short term - Inhalation 1516 mg/m³ <u>Effects:</u> Systemic</p>
2-butoxyethyl acetate	<p>DNEL - Workers - Long term - Inhalation 20 ppm <u>Effects:</u> Systemic</p> <p>DNEL - Workers - Long term - Dermal 102 mg/kg bw/day <u>Effects:</u> Systemic</p> <p>DNEL - Workers - Long term - Inhalation 133 mg/m³ <u>Effects:</u> Systemic</p> <p>DNEL - General population - Long term - Oral 8.6 mg/kg bw/day <u>Effects:</u> Systemic</p> <p>DNEL - General population - Short term - Oral 36 mg/kg bw/day <u>Effects:</u> Systemic</p> <p>DNEL - General population - Short term - Dermal 72 mg/kg bw/day <u>Effects:</u> Systemic</p> <p>DNEL - General population - Long term - Dermal</p>

SECTION 8: Exposure controls/personal protection

	102 mg/kg bw/day <u>Effects:</u> Systemic
	DNEL - Workers - Short term - Dermal 120 mg/kg bw/day <u>Effects:</u> Systemic
	DNEL - Workers - Long term - Dermal 169 mg/kg bw/day <u>Effects:</u> Systemic
	DNEL - Workers - Short term - Inhalation 333 mg/m ³ <u>Effects:</u> Local
2-hydroxyethyl methacrylate	DNEL - Workers - Long term - Inhalation 0.908 ppm <u>Effects:</u> Systemic
	DNEL - General population - Long term - Oral 0.83 mg/kg bw/day <u>Effects:</u> Systemic
	DNEL - General population - Long term - Dermal 0.83 mg/kg bw/day <u>Effects:</u> Systemic
	DNEL - Workers - Long term - Dermal 1.39 mg/kg bw/day <u>Effects:</u> Systemic
	DNEL - General population - Long term - Inhalation 1.45 mg/m ³ <u>Effects:</u> Systemic
	DNEL - Workers - Long term - Inhalation 4.9 mg/m ³ <u>Effects:</u> Systemic
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3	DNEL - Workers - Long term - Inhalation 0.35 mg/m ³ <u>Effects:</u> Systemic
	DNEL - Workers - Long term - Dermal 0.5 mg/kg <u>Effects:</u> Systemic
	DNEL - General population - Long term - Inhalation 0.085 mg/m ³ <u>Effects:</u> Systemic
	DNEL - General population - Long term - Dermal 0.25 mg/kg <u>Effects:</u> Systemic
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl	DNEL - Workers - Long term - Inhalation 3.53 mg/m ³

SECTION 8: Exposure controls/personal protection

1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Effects: Systemic

DNEL - Workers - Long term - Dermal

2 mg/kg

Effects: Systemic

DNEL - General population - Long term - Oral

0.18 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.31 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

0.9 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

1.27 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

1.8 mg/kg bw/day

Effects: Systemic

PNECs

Product/ingredient name

n-butyl acetate

Result

Soil

0.09 mg/kg

Fresh water

0.18 mg/l

Sewage Treatment Plant

35.6 mg/l

Marine water

0.018 mg/l

Fresh water sediment

0.981 mg/kg

Marine water sediment

0.098 mg/kg

4-methylpentan-2-one

Marine water

0.06 mg/l

Fresh water

0.6 mg/l

Sediment

8.27 mg/kg

2-butoxyethyl acetate

Fresh water

SECTION 8: Exposure controls/personal protection

	0.304 mg/l
	Marine water 0.0304 mg/l
	Fresh water sediment 2.03 mg/kg dwt
	Marine water sediment 0.203 mg/kg dwt
	Soil 0.415 mg/kg dwt
	Sewage Treatment Plant 90 mg/l
2-hydroxyethyl methacrylate	Fresh water 0.482 mg/l
	Marine water 0.0482 mg/l
	Sewage Treatment Plant 10 mg/l
	Fresh water sediment 1.98 mg/kg dwt
	Marine water sediment 0.198 mg/kg dwt
	Soil 0.113 mg/kg dwt
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3	Fresh water 0.0023 mg/l
	Marine water 0.00023 mg/l
	Sewage Treatment Plant 10 mg/l
	Fresh water sediment 3.37 mg/kg
	Marine water sediment 0.337 mg/kg
	Soil 2 mg/kg
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Fresh water 0.0022 mg/l

SECTION 8: Exposure controls/personal protection

Marine water

0.00022 mg/l

Secondary Poisoning

0.009 mg/l

Fresh water sediment

1.05 mg/kg

Marine water sediment

0.11 mg/kg

Soil

0.21 mg/kg

Sewage Treatment Plant

1 mg/l

8.2 Exposure controls

Appropriate engineering controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Use safety eyewear designed to protect against splash of liquids.

Skin protection

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves : Duration / breakthrough time: <1 hour,
Glove material: NBR, nitrile rubber, material thickness as splash protection: at least 0.2 mm, (EN374)
Glove material: NBR, nitrile rubber Material thickness for short-term contact: at least 0.5 mm, (EN374)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

Expert judgment

SECTION 8: Exposure controls/personal protection

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
A management program to ensure safe use including proper fitting, training on handling, duration of use, cleaning and replacement of respirators must be in place.
Recommended:
EN 140 filter mask with AXP3 or ABEK2P3 filter according to EN 14387 or pressurized air respirator according to EN 14594.
Depending on the risk assessment of the workplace, other respirator types might be selected.
- Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
- Environmental exposure controls** : Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Clear.
- Odour** : Not available.
- Odour threshold** : Not available.
- Melting point/freezing point** : Technically not possible to measure
- Boiling point or initial boiling point and boiling range** : 114 to 200°C
- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: 0.7%
Upper: 8%
- Lower and upper explosive (flammable) limits** : Not available.
- Flash point** : Closed cup: 14°C
- Auto-ignition temperature** : 280°C
- Decomposition temperature** : Not applicable.
- pH** : Not applicable.
- Justification** : Product is non-soluble (in water).
- Viscosity** : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): 5.2 mm²/s

SECTION 9: Physical and chemical properties

Vapour pressure	0.64 kPa (4.82 mm Hg)	
Density	: 0.98 g/cm ³	
Weight volatiles	: 49.3 % (w/w)	
VOC content	: 48.6 % (w/w)	(2010/75/EU)

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Further information Not available.

9.2.2 Other safety characteristics

Miscible with water : No.

Further information Not available.

room temperature (=20°C)

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

SECTION 11: Toxicological information

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-hydroxyethyl methacrylate, reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly(oxyethylene) and α -3, Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result
n-butyl acetate	Rat - Oral - LD50 10768 mg/kg <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Other changes Liver - Other changes
-	Rabbit - Dermal - LD50 >17600 mg/kg
-	Rat - Inhalation - LC50 Vapour 21.1 mg/l [4 hours]
4-methylpentan-2-one	Rat - Oral - LD50 2080 mg/kg
-	Rat - Inhalation - LC50 Vapour 16.4 mg/l [4 hours]
Hydrocarbons, C9, aromatics	Rat - Female - Oral - LD50 3492 mg/kg OECD 401
-	Rabbit - Dermal - LD50 >3160 mg/kg OECD 402
heptan-2-one	Rat - Oral - LD50 1600 mg/kg <u>Toxic effects:</u> Behavioral - Ataxia Lung, Thorax, or Respiration - Respiratory depression
-	Rabbit - Dermal - LD50 10332 mg/kg
-	Rat - Inhalation - LC50 Vapour 16.8 mg/l [4 hours]
2-butoxyethyl acetate	Rabbit - Dermal - LD50 1500 mg/kg <u>Toxic effects:</u> Kidney, Ureter, and Bladder - Hematuria Kidney, Ureter, and Bladder - Other changes in urine composition Blood - Normocytic anemia
-	Rat - Male, Female - Oral - LD50 1880 mg/kg OECD [Acute Oral Toxicity]
-	Rat - Inhalation - LC50 Vapour

SECTION 11: Toxicological information

	7.82 mg/l [4 hours] OECD [Acute Inhalation Toxicity]
2-hydroxyethyl methacrylate	Rat - Oral - LD50 5050 mg/kg <u>Toxic effects:</u> Behavioral - Coma
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rat - Male, Female - Oral - LD50 3230 mg/kg OECD [Acute Oral toxicity - Acute Toxic Class Method]
-	Rat - Male, Female - Dermal - LD50 >3170 mg/kg OECD [Acute Dermal Toxicity]

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
mixture	18593.4	75530.1	N/A	73.7	N/A
n-butyl acetate	10768	N/A	N/A	21.1	N/A
4-methylpentan-2-one	2080	N/A	N/A	11	N/A
Hydrocarbons, C9, aromatics	3492	N/A	N/A	N/A	N/A
heptan-2-one	1600	10332	N/A	16.8	N/A
2-butoxyethyl acetate	1880	1500	N/A	11	N/A
2-hydroxyethyl methacrylate	5050	N/A	N/A	N/A	N/A
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3230	N/A	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name

4-methylpentan-2-one

Result

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

heptan-2-one

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 14 mg

2-hydroxyethyl methacrylate

Rabbit - Skin - Irritant

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

Result

SECTION 11: Toxicological information

4-methylpentan-2-one

Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 uL

-

Rabbit - Eyes - Severe irritant

Amount/concentration applied: 40 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

n-butyl acetate

4-methylpentan-2-one

Hydrocarbons, C9, aromatics

-

heptan-2-one

Result

STOT SE 3, H336 (Narcotic effects)

STOT SE 3, H336 (Narcotic effects)

STOT SE 3, H335 (Respiratory tract irritation)

STOT SE 3, H336 (Narcotic effects)

STOT SE 3, H336 (Narcotic effects)

Specific target organ toxicity (repeated exposure)

SECTION 11: Toxicological information

Not available.

Aspiration hazard

Product/ingredient name

Hydrocarbons, C9, aromatics

Result

ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact

: No known significant effects or critical hazards.

Inhalation

: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Skin contact

: Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.

Ingestion

: Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

: No specific data.

Inhalation

: Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Skin contact

: Adverse symptoms may include the following:
irritation
redness
dryness
cracking

Ingestion

: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects

: Not available.

Potential delayed effects

: Not available.

Long term exposure

Potential immediate effects

: Not available.

Potential delayed effects

: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General

: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity

: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity

: No known significant effects or critical hazards.

Reproductive toxicity

: No known significant effects or critical hazards.

SECTION 11: Toxicological information

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name

n-butyl acetate

Result

Acute - LC50 - Marine water

Fish - Inland silverside - *Menidia beryllina*

185 ppm [96 hours]

Effect: Mortality

4-methylpentan-2-one

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 29 days; Size: 21 mm; Weight: 0.141 g

505 mg/l [96 hours]

Effect: Mortality

-

Chronic - NOEC - Fresh water

Daphnia - Water flea - *Daphnia magna*

78 mg/l [21 days]

Effect: Behavior

-

Chronic - NOEC - Fresh water

Fish - Fathead minnow - *Pimephales promelas* - Embryo

Age: <24 hours

168 mg/l [33 days]

Effect: Mortality

Hydrocarbons, C9, aromatics

Acute - LC50

OECD 203

Fish - Trout - *Oncorhynchus mykiss*

9.2 mg/l [96 hours]

heptan-2-one

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 32 days; Size: 18.4 mm; Weight: 0.095 g

131 mg/l [96 hours]

Effect: Mortality

2-butoxyethyl acetate

Chronic - LC50

Fish - Trout

11 mg/l [96 hours]

SECTION 12: Ecological information

2-hydroxyethyl methacrylate

Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas* - Juvenile (Fledgling, Hatchling, Weanling)

Age: 28 to 34 days; Size: 20.9 mm; Weight: 0.134 g
227 mg/l [96 hours]

Effect: Mortality

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3

Acute - LC50

OECD 203

Fish

2.8 mg/l [96 hours]

-

Acute - EC50

Daphnia

4 mg/l [48 hours]

-

Acute - EC50

OECD 201

Aquatic plants

>100 mg/l [72 hours]

-

Acute - EC50

Micro-organism

>1000 mg/l [3 hours]

-

Chronic - NOEC

OECD 202

Daphnia

0.78 mg/l [21 days]

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Acute - LC50

OECD 203, semistatic

Fish - *Brachydanio rerio*

0.9 mg/l [96 hours]

-

Chronic - NOEC - Fresh water

OECD [Daphnia Magna Reproduction Test]

Daphnia

1 mg/l [21 days]

-

Acute - EC50 - Fresh water

OECD [Alga, Growth Inhibition Test]

Algae

1.68 mg/l [72 hours]

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name

2-butoxyethyl acetate

Result

>60% [28 days] - Readily

Conclusion/Summary [Product] : Not available.

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-butoxyethyl acetate	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
n-butyl acetate	2.3	-	Low
4-methylpentan-2-one	1.9	-	Low
heptan-2-one	2.26	-	Low
2-butoxyethyl acetate	1.51	-	Low
2-hydroxyethyl methacrylate	0.42	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
n-butyl acetate	1.5	33.2139
4-methylpentan-2-one	1.6	40.9047
heptan-2-one	1.6	39.9018
2-butoxyethyl acetate	2.1	112.842
2-hydroxyethyl methacrylate	1.3	20.9282

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
n-butyl acetate	No	N/A	Yes	No	N/A	N/A	Yes
4-methylpentan-2-one	No	N/A	Yes	No	N/A	N/A	Yes
Hydrocarbons, C9, aromatics	No	No	No	No	No	No	No
heptan-2-one	No	N/A	Yes	No	N/A	N/A	Yes
2-butoxyethyl acetate	No	N/A	Yes	No	No	N/A	No
2-hydroxyethyl methacrylate	No	N/A	Yes	No	N/A	N/A	Yes
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly(oxyethylene) and α -3	No	No	No	No	No	No	No
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
n-butyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
4-methylpentan-2-one	No	N/A	N/A	No	N/A	N/A	N/A
Hydrocarbons, C9, aromatics	No	N/A	N/A	No	N/A	N/A	N/A
heptan-2-one	No	N/A	N/A	No	N/A	N/A	N/A
2-butoxyethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
2-hydroxyethyl methacrylate	No	N/A	N/A	No	N/A	N/A	N/A
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly (oxyethylene) and α -3	No	N/A	N/A	No	N/A	N/A	N/A
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
n-butyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
4-methylpentan-2-one	No	N/A	N/A	No	N/A	N/A	N/A
Hydrocarbons, C9, aromatics	No	No	No	No	No	No	No
heptan-2-one	No	N/A	N/A	No	N/A	N/A	N/A
2-butoxyethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
2-hydroxyethyl methacrylate	No	N/A	N/A	No	N/A	N/A	N/A
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly (oxyethylene) and α -3	No	No	No	No	No	No	No
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.
Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.
- Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.





Packaging

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging	European waste catalogue (EWC)	
CEPE Guidelines	15 01 10*	packaging containing residues of or contaminated by hazardous substances

- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3 	3 	3 	3 

SECTION 14: Transport information

14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADR/RID	: Special provisions 640 (D) Tunnel code (D/E)
ADN	: The product is only regulated as an environmentally hazardous substance when transported in tank vessels. Special provisions 640 (D)
Marine pollutant	Not available.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
mixture	≥90	3

Labelling : Not applicable.

Other EU regulations

Explosive precursors : Not applicable.

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

National regulations

SECTION 15: Regulatory information

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

Flammable liquid class (SRVFS 2005:10) : 1

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

CEPE code : 1

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 B = Bioaccumulative
 BCF = Bioconcentration Factor
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 IATA = International Air Transport Association
 IMDG = International Maritime Dangerous Goods
 IMO = International Maritime Organization
 M = Mobile
 N/A = Not available
 P = Persistent
 PBT = Persistent, Bioaccumulative and Toxic
 PMT = Persistent, Mobile and Toxic
 PNEC = Predicted No Effect Concentration
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SGG = Segregation Group
 T = Toxic
 vB = Very Bioaccumulative
 vM = Very Mobile
 vP = Very Persistent
 vPvB = Very Persistent and Very Bioaccumulative
 vPvM = Very Persistent and Very Mobile

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 2, H225 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H336 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method Calculation method Calculation method

SECTION 16: Other information

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 19 February 2026

Version : 1

Date of previous issue : No previous validation

Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by

SECTION 16: Other information

applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2026 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.