
SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product identifier : TRIMSTW/AL
Product name : TRIM #11 STEEL WHEELS HIGH BUILD TOPCOAT AEROSOL
Product type : Aerosol.
Appearance : Aerosol.
Other means of identification : Not available.
Date of issue/ Date of revision : 19 February 2026
Version : 1.01
Date of previous issue : 1 October 2025

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Coating component.
Uses advised against : Not for sale to or use by consumers.

1.3 Details of the supplier of the safety data sheet

U-POL NETHERLANDS B.V,
DE GEER 14,
4004LT TIEL,
NETHERLANDS
+31 20 240 2216
sds-competence@axalta.com

e-mail address of person responsible for this SDS : sds-competence@axalta.com

National contact

U-POL LTD,
DENINGTON ROAD,
WELLINGBOROUGH,
NN8 2QH
+44 (0) 1933 230310
sds-competence@axalta.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : 010-456 6700 (9:00-17:00);112

Supplier

+(44)-870-8200418

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aerosol 1, H222, H229

Eye Irrit. 2, H319

Carc. 2, H351

STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Contains : acetone
4-methylpentan-2-one

Hazard statements : H222, H229 - Extremely flammable aerosol. Pressurised container: may burst if heated.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H351 - Suspected of causing cancer.

Precautionary statements

Prevention : P201 - Obtain special instructions before use.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.

Response : P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage : P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Disposal : Not applicable.

Supplemental label elements : EUH066 - Repeated exposure may cause skin dryness or cracking.
EUH208 - Contains reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3 and Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

2.3 Other hazards

SECTION 2: Hazards identification

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Dimethyl ether	REACH #: 01-2119472128-37 EC: 204-065-8 CAS: 115-10-6 Index: 603-019-00-8	≥25 - ≤50	Flam. Gas 1A, H220 Press. Gas (Comp.), H280	-	[1] [2]
acetone	REACH #: 01-2119471330-49 EC: 200-662-2 CAS: 67-64-1	≥25 - ≤50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	-	[1] [2]
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4	≤10	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
butanone	REACH #: 01-2119457290-43 EC: 201-159-0 CAS: 78-93-3	≤3	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	-	[1] [2]
Hydrocarbons, C9, aromatics	REACH #: 01-2119455851-35 EC: 918-668-5	<2.5	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	-	[1]
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	REACH #: 01-2119555267-33 EC: 905-562-9 CAS: --	≤3	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1]
Aluminium powder (stabilized)	REACH #: 01-2119529243-45 EC: 231-072-3 CAS: 7429-90-5 Index: 013-002-00-1	≤3	Flam. Sol. 1, H228	-	[1] [2]

SECTION 3: Composition/information on ingredients

2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6	≤3	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
4-methylpentan-2-one	REACH #: 01-2119473980-30 EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	≤3	Flam. Liq. 2, H225 Acute Tox. 4, H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336 EUH066	ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
cyclohexanone	REACH #: 01-2119453616-35 EC: 203-631-1 CAS: 108-94-1 Index: 606-010-00-7	<3	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335	ATE [Oral] = 1800 mg/kg ATE [Dermal] = 1100 mg/kg ATE [Inhalation (gases)] = 8000 ppm	[1] [2]
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-ω-hydroxypoly(oxyethylene) and α-3	REACH #: 01-0000015075-76 EC: 400-830-7	<0.1	Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	<0.1	Skin Sens. 1A, H317 Repr. 2, H361f (oral) Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	M [Acute] = 1 M [Chronic] = 1	[1]

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

SECTION 4: First aid measures

- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3, Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

SECTION 5: Firefighting measures

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

- 6.3 Methods and material for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

- 7.1 Precautions for safe handling** : Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.
- Information on fire and explosion protection**
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P3a	150 tonnes	500 tonnes

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Identifiers	Exposure limit values
dimethyl ether	REACH #: 01-2119472128-37 EC: 204-065-8 CAS: 115-10-6 Index: 603-019-00-8	Work environment authority Regulation 2018:1 (Sweden, 11/2022) TWA 8 hours: 500 ppm. TWA 8 hours: 950 mg/m ³ . STEL 15 minutes: 800 ppm. STEL 15 minutes: 1500 mg/m ³ . EU OEL (Europe, 1/2022) TWA 8 hours: 1000 ppm. TWA 8 hours: 1920 mg/m ³ .
acetone	REACH #: 01-2119471330-49 EC: 200-662-2 CAS: 67-64-1	Work environment authority Regulation 2018:1 (Sweden, 11/2022) TWA 8 hours: 250 ppm. TWA 8 hours: 600 mg/m ³ . STEL 15 minutes: 500 ppm. STEL 15 minutes: 1200 mg/m ³ . EU OEL (Europe, 1/2022) TWA 8 hours: 500 ppm. TWA 8 hours: 1210 mg/m ³ .
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS:	Work environment authority Regulation 2018:1 (Sweden, 11/2022) [butyl acetate] TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m ³ . STEL 15 minutes: 150 ppm.

SECTION 8: Exposure controls/personal protection

butanone	123-86-4 REACH #: 01-2119457290-43 EC: 201-159-0 CAS: 78-93-3	STEL 15 minutes: 723 mg/m ³ . EU OEL (Europe, 1/2022) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ . TWA 8 hours: 241 mg/m ³ . TWA 8 hours: 50 ppm. Work environment authority Regulation 2018:1 (Sweden, 11/2022) TWA 8 hours: 50 ppm. TWA 8 hours: 150 mg/m ³ . STEL 15 minutes: 300 ppm. STEL 15 minutes: 900 mg/m ³ . EU OEL (Europe, 1/2022) TWA 8 hours: 200 ppm. TWA 8 hours: 600 mg/m ³ . STEL 15 minutes: 300 ppm. STEL 15 minutes: 900 mg/m ³ .
Aluminium powder (stabilized)	REACH #: 01-2119529243-45 EC: 231-072-3 CAS: 7429-90-5 Index: 013-002-00-1	Work environment authority Regulation 2018:1 (Sweden, 11/2022) [aluminium, soluble compounds] TWA 8 hours: 1 mg/m ³ (as Al). Form: Total dust. Work environment authority Regulation 2018:1 (Sweden, 11/2022) [aluminium and oxide] TWA 8 hours: 2 mg/m ³ (as Al). Form: respirable fraction. TWA 8 hours: 5 mg/m ³ (as Al). Form: Total dust.
2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6	Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ . EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ .
4-methylpentan-2-one	REACH #: 01-2119473980-30 EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	Work environment authority Regulation 2018:1 (Sweden, 11/2022) TWA 8 hours: 20 ppm. TWA 8 hours: 83 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 200 mg/m ³ . EU OEL (Europe, 1/2022) TWA 8 hours: 20 ppm. TWA 8 hours: 83 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 208 mg/m ³ .
cyclohexanone	REACH #: 01-2119453616-35 EC: 203-631-1 CAS: 108-94-1 Index: 606-010-00-7	Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. TWA 8 hours: 10 ppm. TWA 8 hours: 41 mg/m ³ . STEL 15 minutes: 20 ppm. STEL 15 minutes: 81 mg/m ³ . EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 10 ppm.

SECTION 8: Exposure controls/personal protection

		TWA 8 hours: 40.8 mg/m ³ . STEL 15 minutes: 20 ppm. STEL 15 minutes: 81.6 mg/m ³ .
--	--	--

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

dimethyl ether

Result

DNEL - General population - Long term - Inhalation

471 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

1894 mg/m³

Effects: Systemic

acetone

DNEL - Workers - Long term - Inhalation

500 ppm

Effects: Systemic

DNEL - Workers - Long term - Dermal

186 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

1210 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

2420 mg/m³

Effects: Local

n-butyl acetate

DNEL - Workers - Short term - Dermal

11 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Oral

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Oral

2 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

SECTION 8: Exposure controls/personal protection

3.4 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Dermal

6 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Short term - Dermal

11 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

12 mg/m³

Effects: Systemic

DNEL - General population - Long term - Inhalation

35.7 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

300 mg/m³

Effects: Local

DNEL - General population - Short term - Inhalation

300 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

300 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

600 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

600 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

300 mg/m³

Effects: Systemic

butanone

DNEL - Workers - Long term - Inhalation

200.539 ppm

Effects: Systemic

DNEL - General population - Long term - Oral

31 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

106 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

412 mg/kg bw/day

SECTION 8: Exposure controls/personal protection

Effects: Systemic

DNEL - General population - Short term - Inhalation

450 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

600 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

900 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

1161 mg/kg bw/day

Effects: Systemic

Hydrocarbons, C9, aromatics

DNEL - Workers - Long term - Inhalation

151 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

12.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

32 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

7.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Oral

7.5 mg/kg bw/day

Effects: Systemic

aluminium powder (stabilised)

DNEL - Workers - Long term - Inhalation

3.72 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

3.72 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

3.95 mg/kg bw/day

Effects: Systemic

2-methoxy-1-methylethyl acetate

DNEL - Workers - Long term - Dermal

796 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

275 mg/m³

Effects: Systemic

SECTION 8: Exposure controls/personal protection

	<p>DNEL - Workers - Short term - Inhalation 550 mg/m³ <u>Effects:</u> Local</p>
	<p>DNEL - General population - Long term - Inhalation 33 mg/m³ <u>Effects:</u> Systemic</p>
	<p>DNEL - General population - Long term - Inhalation 33 mg/m³ <u>Effects:</u> Local</p>
	<p>DNEL - General population - Long term - Dermal 320 mg/kg bw/day <u>Effects:</u> Systemic</p>
	<p>DNEL - General population - Long term - Oral 36 mg/kg bw/day <u>Effects:</u> Systemic</p>
	<p>DNEL - General population - Short term - Oral 500 mg/kg bw/day <u>Effects:</u> Systemic</p>
4-methylpentan-2-one	<p>DNEL - Workers - Long term - Dermal 11.8 mg/kg bw/day <u>Effects:</u> Systemic</p> <p>DNEL - Workers - Long term - Inhalation 83 mg/m³ <u>Effects:</u> Local</p> <p>DNEL - Workers - Long term - Inhalation 83 mg/m³ <u>Effects:</u> Systemic</p> <p>DNEL - Workers - Short term - Inhalation 208 mg/m³ <u>Effects:</u> Local</p> <p>DNEL - Workers - Short term - Inhalation 208 mg/m³ <u>Effects:</u> Systemic</p> <p>DNEL - General population - Long term - Oral 4.2 mg/kg bw/day <u>Effects:</u> Systemic</p>
cyclohexanone	<p>DNEL - Workers - Long term - Inhalation 9.8 ppm <u>Effects:</u> Systemic</p> <p>DNEL - General population - Short term - Dermal 1 mg/kg bw/day <u>Effects:</u> Systemic</p> <p>DNEL - General population - Long term - Dermal</p>

SECTION 8: Exposure controls/personal protection

1 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Oral

1.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Oral

1.5 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

2.55 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Dermal

4 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

4 mg/kg bw/day

Effects: Systemic

DNEL - General population - Short term - Inhalation

5 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

10 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

10 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

20 mg/m³

Effects: Local

DNEL - Workers - Short term - Inhalation

20 mg/m³

Effects: Systemic

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3

DNEL - Workers - Long term - Inhalation

0.35 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.5 mg/kg

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.085 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

0.25 mg/kg

SECTION 8: Exposure controls/personal protection

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Effects: Systemic

DNEL - Workers - Long term - Inhalation

3.53 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

2 mg/kg

Effects: Systemic

DNEL - General population - Long term - Oral

0.18 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.31 mg/m³

Effects: Systemic

DNEL - General population - Long term - Dermal

0.9 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

1.27 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Dermal

1.8 mg/kg bw/day

Effects: Systemic

PNECs

Product/ingredient name

acetone

Result

Fresh water

10.6 mg/l

Marine water sediment

1.06 mg/l

Sediment

30.4 mg/kg

Marine water sediment

3.04 mg/kg

Soil

29.5 mg/kg

Sewage Treatment Plant

100 mg/l

n-butyl acetate

Soil

0.09 mg/kg

Fresh water

0.18 mg/l

SECTION 8: Exposure controls/personal protection

	Sewage Treatment Plant 35.6 mg/l
	Marine water 0.018 mg/l
	Fresh water sediment 0.981 mg/kg
	Marine water sediment 0.098 mg/kg
butanone	Fresh water 55.8 mg/l
	Sewage Treatment Plant 709 mg/l
	Fresh water sediment 284.7 mg/kg
	Marine water sediment 284.7 mg/kg
	Marine water 55.8 mg/l
	Sewage Treatment Plant 22.5 mg/kg
aluminium powder (stabilised)	Fresh water 0.0749 mg/l
	Sewage Treatment Plant 20 mg/l
2-methoxy-1-methylethyl acetate	Fresh water 0.635 mg/l
	Marine water 0.0635 mg/l
	Sewage Treatment Plant 100 mg/l
	Fresh water sediment 3.29 mg/kg dwt
	Marine water sediment 0.329 mg/kg dwt
	Soil 0.29 mg/kg dwt
4-methylpentan-2-one	Marine water 0.06 mg/l
	Fresh water

SECTION 8: Exposure controls/personal protection

	0.6 mg/l
	Sediment 8.27 mg/kg
cyclohexanone	Fresh water 0.0329 mg/l
	Marine water 0.0329 mg/l
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3	Fresh water 0.0023 mg/l
	Marine water 0.00023 mg/l
	Sewage Treatment Plant 10 mg/l
	Fresh water sediment 3.37 mg/kg
	Marine water sediment 0.337 mg/kg
	Soil 2 mg/kg
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Fresh water 0.0022 mg/l
	Marine water 0.00022 mg/l
	Secondary Poisoning 0.009 mg/l
	Fresh water sediment 1.05 mg/kg
	Marine water sediment 0.11 mg/kg
	Soil 0.21 mg/kg
	Sewage Treatment Plant 1 mg/l

8.2 Exposure controls

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Use safety eyewear designed to protect against splash of liquids.

Skin protection

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves : Duration / breakthrough time: <1 hour,
Glove material: NBR, nitrile rubber, material thickness as splash protection: at least 0.2 mm, (EN374)
Glove material: NBR, nitrile rubber Material thickness for short-term contact: at least 0.5 mm, (EN374)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

Expert judgment

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
A management program to ensure safe use including proper fitting, training on handling, duration of use, cleaning and replacement of respirators must be in place.
Recommended:
EN 140 filter mask with AXP3 or ABEK2P3 filter according to EN 14387 or pressurized air respirator according to EN 14594.
Depending on the risk assessment of the workplace, other respirator types might be selected.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable

SECTION 8: Exposure controls/personal protection

respiratory protective equipment should be used.

Environmental exposure controls : Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Colour	: Silver.
Odour	: Characteristic.
Odour threshold	: Not available.
Melting point/freezing point	: Technically not possible to measure
Boiling point or initial boiling point and boiling range	: Not applicable.
Flammability	: Not available.
Lower and upper explosion limit	: Lower: 1.2% Upper: 26.2%
Lower and upper explosive (flammable) limits	: Not available.
Flash point	: Closed cup: -41°C
Auto-ignition temperature	: 280°C
Decomposition temperature	: Not applicable.
pH	: Not applicable.
Justification	: Product is non-polar/aprotic.
Viscosity	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): Not available.
Vapour pressure	237.5 kPa (1781.03 mm Hg)
Density	: 0.765 g/cm ³
Weight volatiles	: 91.7 % (w/w)
VOC content	: 91.7 % (w/w) (2010/75/EU)

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Heat of combustion : 25.86 kJ/g

Aerosol product

Type of aerosol : Spray

Mixture does not react with water.

Further information Not available.

9.2.2 Other safety characteristics

Miscible with water : Yes.

Further information Not available.

SECTION 9: Physical and chemical properties

room temperature (=20°C)

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3, Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result
-------------------------	--------

SECTION 11: Toxicological information

dimethyl ether	Rat - Oral - LD50 >99999 mg/kg
-	Rat - Dermal - LD50 >99999 mg/kg
-	Rat - Inhalation - LC50 Vapour 309 g/m ³ [4 hours]
-	Rat - Inhalation - LC50 Gas. 164000 ppm [4 hours] <u>Toxic effects:</u> Behavioral - Ataxia Behavioral - Coma
acetone	Rat - Oral - LD50 5800 mg/kg <u>Toxic effects:</u> Behavioral - Altered sleep time (including change in righting reflex) Behavioral - Tremor
-	Rabbit - Dermal - LD50 2001 mg/kg
-	Rat - Inhalation - LC50 Vapour 21 mg/l [4 hours]
n-butyl acetate	Rat - Oral - LD50 10768 mg/kg <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Other changes Liver - Other changes
-	Rabbit - Dermal - LD50 >17600 mg/kg
-	Rat - Inhalation - LC50 Vapour 21.1 mg/l [4 hours]
butanone	Rabbit - Dermal - LD50 6480 mg/kg
-	Rat - Oral - LD50 2737 mg/kg
Hydrocarbons, C9, aromatics	Rat - Female - Oral - LD50 3492 mg/kg OECD 401
-	Rabbit - Dermal - LD50 >3160 mg/kg OECD 402
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	Rat - Male, Female - Oral - LD50 3523 mg/kg EU B.1
-	Rabbit - Male - Dermal - LD50 12126 mg/kg EU B.1

SECTION 11: Toxicological information

-	Rat - Male - Inhalation - LC50 Vapour 6350 ppm [4 hours] EU B.2
4-methylpentan-2-one	Rat - Oral - LD50 2080 mg/kg
-	Rat - Inhalation - LC50 Vapour 16.4 mg/l [4 hours]
cyclohexanone	Rat - Oral - LD50 1800 mg/kg
-	Rat - Inhalation - LC50 Gas. 8000 ppm [4 hours]
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rat - Male, Female - Oral - LD50 3230 mg/kg OECD [Acute Oral toxicity - Acute Toxic Class Method]
-	Rat - Male, Female - Dermal - LD50 >3170 mg/kg OECD [Acute Dermal Toxicity]

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
mixture	153846.2	35908.3	683760.7	319.0	N/A
dimethyl ether	N/A	N/A	164000	309	N/A
acetone	5800	2001	N/A	21	N/A
n-butyl acetate	10768	N/A	N/A	21.1	N/A
butanone	2737	6480	N/A	N/A	N/A
Hydrocarbons, C9, aromatics	3492	N/A	N/A	N/A	N/A
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	3523	1100	N/A	11	N/A
4-methylpentan-2-one	2080	N/A	N/A	11	N/A
cyclohexanone	1800	1100	8000	N/A	N/A
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3230	N/A	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name
acetone

Result

Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

- **Rabbit - Skin - Mild irritant**
Amount/concentration applied: 395 mg

SECTION 11: Toxicological information

butanone	Rabbit - Skin - Mild irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 14 mg
-	Rabbit - Skin - Mild irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 402 mg
-	Rabbit - Skin - Moderate irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 500 mg
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	Rabbit - Skin - Irritant EU B.4 <u>Duration of treatment/exposure:</u> 4 hours <u>Observation period:</u> 7 days
4-methylpentan-2-one	Rabbit - Skin - Mild irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 500 mg
cyclohexanone	Human - Skin - Mild irritant <u>Duration of treatment/exposure:</u> 48 hours <u>Amount/concentration applied:</u> 50 %
-	Rabbit - Skin - Mild irritant <u>Amount/concentration applied:</u> 500 mg
-	Rabbit - Skin - Irritant OECD [Acute Dermal Irritation/Corrosion]

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name	Result
acetone	Human - Eyes - Mild irritant <u>Amount/concentration applied:</u> 186300 ppm
-	Rabbit - Eyes - Mild irritant <u>Amount/concentration applied:</u> 10 uL
-	Rabbit - Eyes - Moderate irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 20 mg
-	Rabbit - Eyes - Severe irritant <u>Amount/concentration applied:</u> 20 mg
4-methylpentan-2-one	Rabbit - Eyes - Moderate irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 100 uL
-	Rabbit - Eyes - Severe irritant <u>Amount/concentration applied:</u> 40 mg
cyclohexanone	Rabbit - Eyes - Severe irritant

SECTION 11: Toxicological information

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 250 ug

- **Rabbit - Eyes - Severe irritant**
Amount/concentration applied: 20 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
acetone	STOT SE 3, H336 (Narcotic effects)
n-butyl acetate	STOT SE 3, H336 (Narcotic effects)
butanone	STOT SE 3, H336 (Narcotic effects)
Hydrocarbons, C9, aromatics	STOT SE 3, H335 (Respiratory tract irritation)
-	STOT SE 3, H336 (Narcotic effects)
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	STOT SE 3, H335 (Respiratory tract irritation)
2-methoxy-1-methylethyl acetate	STOT SE 3, H336 (Narcotic effects)
4-methylpentan-2-one	STOT SE 3, H336 (Narcotic effects)

SECTION 11: Toxicological information

cyclohexanone

STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Product/ingredient name

REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE

Result

STOT RE 2, H373

Aspiration hazard

Product/ingredient name

Hydrocarbons, C9, aromatics
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE

Result

ASPIRATION HAZARD - Category 1
ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

Product/ingredient name

acetone

Result

Acute - LC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*

10 mg/l [48 hours]

Effect: Mortality

-

Chronic - NOEC - Marine water

Algae - Green algae - *Ulva pertusa*

4.95 mg/l [96 hours]

Effect: Reproduction

-

Acute - EC50 - Marine water

Algae - Green algae - *Ulva pertusa*

20.565 mg/l [96 hours]

Effect: Reproduction

-

Chronic - NOEC - Fresh water

Crustaceans - Daphnia - *Daphniidae*

0.016 ml/l [21 days]

Effect: Population

-

Acute - LC50 - Fresh water

Fish - Guppy - *Poecilia reticulata*

Age: 4 to 12 months; Size: 2 to 10 cm; Weight: 0.5 to 14 g
5600 ppm [96 hours]

Effect: Mortality

n-butyl acetate

Acute - LC50 - Marine water

SECTION 12: Ecological information

	<p>Fish - Inland silverside - <i>Menidia beryllina</i> 185 ppm [96 hours] <u>Effect</u>: Mortality</p>
butanone	<p>Acute - EC50 - Fresh water Daphnia - Water flea - <i>Daphnia magna</i> - Larvae <u>Age</u>: <24 hours 5091 mg/l [48 hours] <u>Effect</u>: Intoxication</p>
-	<p>Acute - LC50 - Fresh water Fish - Fathead minnow - <i>Pimephales promelas</i> <u>Age</u>: 31 days; <u>Size</u>: 22 mm; <u>Weight</u>: 0.167 g 3220 mg/l [96 hours] <u>Effect</u>: Mortality</p>
-	<p>Acute - EC50 - Marine water Algae - Diatom - <i>Skeletonema costatum</i> >500 mg/l [96 hours] <u>Effect</u>: Population</p>
Hydrocarbons, C9, aromatics	<p>Acute - LC50 OECD 203 Fish - Trout - <i>Oncorhynchus mykiss</i> 9.2 mg/l [96 hours]</p>
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	<p>Acute - LC50 Fish 2.6 mg/l [96 hours]</p>
-	<p>Acute - EC50 Daphnia 6.14 mg/l [48 hours]</p>
4-methylpentan-2-one	<p>Acute - LC50 - Fresh water Fish - Fathead minnow - <i>Pimephales promelas</i> <u>Age</u>: 29 days; <u>Size</u>: 21 mm; <u>Weight</u>: 0.141 g 505 mg/l [96 hours] <u>Effect</u>: Mortality</p>
-	<p>Chronic - NOEC - Fresh water Daphnia - Water flea - <i>Daphnia magna</i> 78 mg/l [21 days] <u>Effect</u>: Behavior</p>
-	<p>Chronic - NOEC - Fresh water Fish - Fathead minnow - <i>Pimephales promelas</i> - Embryo <u>Age</u>: <24 hours 168 mg/l [33 days] <u>Effect</u>: Mortality</p>
cyclohexanone	<p>Acute - LC50 - Fresh water Fish - Fathead minnow - <i>Pimephales promelas</i> <u>Age</u>: 30 days; <u>Size</u>: 20.2 mm; <u>Weight</u>: 0.127 g 527 mg/l [96 hours] <u>Effect</u>: Mortality</p>

SECTION 12: Ecological information

-	Chronic - EC10 Algae - Green algae - <i>Chlamydomonas reinhardtii</i> - Exponential growth phase Age: 7 days 3.56 mg/l [72 hours] Effect: Population
-	Acute - EC50 Algae - Green algae - <i>Chlamydomonas reinhardtii</i> - Exponential growth phase Age: 7 days 32.9 mg/l [72 hours] Effect: Population
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3	Acute - LC50 OECD 203 Fish 2.8 mg/l [96 hours]
-	Acute - EC50 Daphnia 4 mg/l [48 hours]
-	Acute - EC50 OECD 201 Aquatic plants >100 mg/l [72 hours]
-	Acute - EC50 Micro-organism >1000 mg/l [3 hours]
-	Chronic - NOEC OECD 202 Daphnia 0.78 mg/l [21 days]
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Acute - LC50 OECD 203, semistatic Fish - <i>Brachydanio rerio</i> 0.9 mg/l [96 hours]
-	Chronic - NOEC - Fresh water OECD [Daphnia Magna Reproduction Test] Daphnia 1 mg/l [21 days]
-	Acute - EC50 - Fresh water OECD [Alga, Growth Inhibition Test] Algae 1.68 mg/l [72 hours]

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name	Result
-------------------------	--------

SECTION 12: Ecological information

REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE

Aerobic
OECD 301F
94% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
dimethyl ether	0.07	-	Low
acetone	-0.23	-	Low
n-butyl acetate	2.3	-	Low
butanone	0.3	-	Low
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	-	25.9	Low
4-methylpentan-2-one	1.9	-	Low
cyclohexanone	0.86	-	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
dimethyl ether	0.44	2.76229
acetone	0.56	3.6548
n-butyl acetate	1.5	33.2139
butanone	1.2	15.8984
4-methylpentan-2-one	1.6	40.9047
cyclohexanone	1.8	63.2873

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
dimethyl ether	No	N/A	Yes	No	N/A	N/A	Yes
acetone	No	N/A	Yes	No	N/A	N/A	Yes
n-butyl acetate	No	N/A	Yes	No	N/A	N/A	Yes
butanone	No	N/A	Yes	No	N/A	N/A	Yes
Hydrocarbons, C9, aromatics	No	No	No	No	No	No	No
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	N/A	N/A	N/A	Yes	N/A	N/A	N/A
Aluminium powder (stabilized)	No	No	No	No	No	No	No
2-methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
4-methylpentan-2-one	No	N/A	Yes	No	N/A	N/A	Yes
cyclohexanone	No	N/A	Yes	No	N/A	N/A	Yes
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-	No	No	No	No	No	No	No

SECTION 12: Ecological information

butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly (oxyethylene) and α -3 Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A
---	-----	-----	-----	-----	-----	-----	-----

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
dimethyl ether	No	N/A	N/A	No	N/A	N/A	N/A
acetone	No	N/A	N/A	No	N/A	N/A	N/A
n-butyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
butanone	No	N/A	N/A	No	N/A	N/A	N/A
Hydrocarbons, C9, aromatics	No	N/A	N/A	No	N/A	N/A	N/A
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	No	N/A	No	Yes	No	N/A	No
Aluminium powder (stabilized)	No	No	No	No	No	No	No
2-methoxy-1-methylethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
4-methylpentan-2-one	No	N/A	N/A	No	N/A	N/A	N/A
cyclohexanone	No	N/A	N/A	No	N/A	N/A	N/A
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly (oxyethylene) and α -3	No	N/A	N/A	No	N/A	N/A	N/A
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
dimethyl ether	No	N/A	N/A	No	N/A	N/A	N/A
acetone	No	N/A	N/A	No	N/A	N/A	N/A
n-butyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
butanone	No	N/A	N/A	No	N/A	N/A	N/A
Hydrocarbons, C9, aromatics	No	No	No	No	No	No	No
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	No	N/A	No	Yes	No	N/A	No
aluminium powder (stabilised)	No	No	No	No	No	No	No

SECTION 12: Ecological information

2-methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
4-methylpentan-2-one	No	N/A	N/A	No	N/A	N/A	N/A
cyclohexanone	No	N/A	N/A	No	N/A	N/A	N/A
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly (oxyethylene) and α -3	No	No	No	No	No	No	No
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.
- Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.





SECTION 13: Disposal considerations

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging	European waste catalogue (EWC)
CEPE Guidelines	15 01 10* packaging containing residues of or contaminated by hazardous substances

Special precautions : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1950	UN1950	UN1950	UN1950
14.2 UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3 Transport hazard class(es)	2 	2 	2.1 	2.1 
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADR/RID : **Tunnel code** (D)

ADN : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.

Marine pollutant : Not available.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
mixture	≥90	3

Labelling : Not applicable.

Other EU regulations

Explosive precursors : This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

National regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

Flammable liquid class (SRVFS 2005:10) : 1

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

CEPE code : 1

🔍 Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 B = Bioaccumulative
 BCF = Bioconcentration Factor
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 IATA = International Air Transport Association

SECTION 16: Other information

IMDG = International Maritime Dangerous Goods
 IMO = International Maritime Organization
 M = Mobile
 N/A = Not available
 P = Persistent
 PBT = Persistent, Bioaccumulative and Toxic
 PMT = Persistent, Mobile and Toxic
 PNEC = Predicted No Effect Concentration
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SGG = Segregation Group
 T = Toxic
 vB = Very Bioaccumulative
 vM = Very Mobile
 vP = Very Persistent
 vPvB = Very Persistent and Very Bioaccumulative
 vPvM = Very Persistent and Very Mobile

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aerosol 1, H222, H229 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336	On basis of test data Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H220 H222, H229	Extremely flammable gas. Extremely flammable aerosol. Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

SECTION 16: Other information

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aerosol 1	AEROSOLS - Category 1
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Gas 1A	FLAMMABLE GASES - Category 1A
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Flam. Sol. 1	FLAMMABLE SOLIDS - Category 1
Press. Gas (Comp.)	GASES UNDER PRESSURE - Compressed gas
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 19 February 2026

Version : 1.01

Date of previous issue : 1 October 2025

Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2026 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.