
SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product identifier : EGCB100
Product name : EGCB100 ACRYLIC PAINT BINDER
Product type : Liquid.
Other means of identification : EGCB100/4
Date of issue/ Date of revision : 19 February 2026
Version : 1.04
Date of previous issue : 19 February 2026

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Coating component.
Uses advised against : Not for sale to or use by consumers.

1.3 Details of the supplier of the safety data sheet

U-POL NETHERLANDS B.V,
DE GEER 14,
4004LT TIEL,
NETHERLANDS
+31 20 240 2216
sds-competence@axalta.com

e-mail address of person responsible for this SDS : sds-competence@axalta.com

National contact

U-POL LTD,
DENINGTON ROAD,
WELLINGBOROUGH,
NN8 2QH
+44 (0) 1933 230310
sds-competence@axalta.com

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : 010-456 6700 (9:00-17:00);112

Supplier

+(44)-870-8200418

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Carc. 2, H351

STOT SE 3, H335

STOT SE 3, H336

STOT RE 2, H373

Asp. Tox. 1, H304

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Contains : Reaction mass of ethylbenzene and xylene
Hydrocarbons, C9, aromatics
4-methylpentan-2-one
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)
propionyl- ω -hydroxypoly(oxyethylene) and α -3
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl
1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Hazard statements : H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H351 - Suspected of causing cancer.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P201 - Obtain special instructions before use.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 - Do not breathe vapour.

Response : P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage : Not applicable.

Disposal : Not applicable.

SECTION 2: Hazards identification

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Reaction mass of ethylbenzene and xylene	REACH #: 01-2119539452-40 EC: 905-588-0	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1]
Hydrocarbons, C9, aromatics	REACH #: 01-2119455851-35 EC: 918-668-5	≤10	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	-	[1]
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4	≤10	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
4-methylpentan-2-one	REACH #: 01-2119473980-30 EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	≤10	Flam. Liq. 2, H225 Acute Tox. 4, H332 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H336 EUH066	ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]

SECTION 3: Composition/information on ingredients

2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6	≤5	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	REACH #: 01-211955267-33 EC: 905-562-9 CAS: --	≤5	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1]
2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6	≤3	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-ω-hydroxypoly (oxyethylene) and α-3	REACH #: 01-0000015075-76 EC: 400-830-7	<1	Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≤0.3	Skin Sens. 1A, H317 Repr. 2, H361f (oral) Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	M [Acute] = 1 M [Chronic] = 1	[1]

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

SECTION 4: First aid measures

4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

SECTION 4: First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3, Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Recommended: alcohol-resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

SECTION 5: Firefighting measures

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling : Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

Information on fire and explosion protection
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

SECTION 7: Handling and storage

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Identifiers	Exposure limit values
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4	Work environment authority Regulation 2018:1 (Sweden, 11/2022) [butyl acetate] TWA 8 hours: 50 ppm. TWA 8 hours: 241 mg/m ³ . STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ . EU OEL (Europe, 1/2022) STEL 15 minutes: 150 ppm. STEL 15 minutes: 723 mg/m ³ . TWA 8 hours: 241 mg/m ³ . TWA 8 hours: 50 ppm.
4-methylpentan-2-one	REACH #: 01-2119473980-30 EC: 203-550-1 CAS: 108-10-1 Index: 606-004-00-4	Work environment authority Regulation 2018:1 (Sweden, 11/2022) TWA 8 hours: 20 ppm. TWA 8 hours: 83 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 200 mg/m ³ . EU OEL (Europe, 1/2022) TWA 8 hours: 20 ppm. TWA 8 hours: 83 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 208 mg/m ³ .
2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC:	Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. TWA 8 hours: 50 ppm.

SECTION 8: Exposure controls/personal protection

2-methoxy-1-methylethyl acetate	203-603-9 CAS: 108-65-6 REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6	TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ . EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ . Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ . EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 275 mg/m ³ . STEL 15 minutes: 100 ppm. STEL 15 minutes: 550 mg/m ³ .
---------------------------------	---	--

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Result
Reaction mass of ethylbenzene and xylene	DNEL - Workers - Long term - Dermal 212 mg/kg bw/day <u>Effects:</u> Systemic
	DNEL - Workers - Long term - Inhalation 221 mg/m ³ <u>Effects:</u> Systemic
Hydrocarbons, C9, aromatics	DNEL - Workers - Long term - Inhalation 151 mg/m ³ <u>Effects:</u> Systemic
	DNEL - Workers - Long term - Dermal 12.5 mg/kg bw/day <u>Effects:</u> Systemic
	DNEL - General population - Long term - Inhalation 32 mg/m ³ <u>Effects:</u> Systemic
	DNEL - General population - Long term - Dermal

SECTION 8: Exposure controls/personal protection

n-butyl acetate

7.5 mg/kg bw/day

Effects: Systemic**DNEL - General population - Long term - Oral**

7.5 mg/kg bw/day

Effects: Systemic**DNEL - Workers - Short term - Dermal**

11 mg/kg bw/day

Effects: Systemic**DNEL - General population - Long term - Oral**

2 mg/kg bw/day

Effects: Systemic**DNEL - General population - Short term - Oral**

2 mg/kg bw/day

Effects: Systemic**DNEL - General population - Long term - Dermal**

3.4 mg/kg bw/day

Effects: Systemic**DNEL - General population - Short term - Dermal**

6 mg/kg bw/day

Effects: Systemic**DNEL - Workers - Short term - Dermal**

11 mg/kg bw/day

Effects: Systemic**DNEL - General population - Long term - Inhalation**12 mg/m³Effects: Systemic**DNEL - General population - Long term - Inhalation**35.7 mg/m³Effects: Local**DNEL - General population - Short term - Inhalation**300 mg/m³Effects: Local**DNEL - General population - Short term - Inhalation**300 mg/m³Effects: Systemic**DNEL - Workers - Long term - Inhalation**300 mg/m³Effects: Local**DNEL - Workers - Short term - Inhalation**600 mg/m³Effects: Local**DNEL - Workers - Short term - Inhalation**600 mg/m³

SECTION 8: Exposure controls/personal protection

	<u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 300 mg/m ³ <u>Effects</u> : Systemic
4-methylpentan-2-one	DNEL - Workers - Long term - Dermal 11.8 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 83 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Inhalation 83 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Short term - Inhalation 208 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Short term - Inhalation 208 mg/m ³ <u>Effects</u> : Systemic
	DNEL - General population - Long term - Oral 4.2 mg/kg bw/day <u>Effects</u> : Systemic
2-methoxy-1-methylethyl acetate	DNEL - Workers - Long term - Inhalation 50.132 ppm <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 796 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 33 mg/m ³ <u>Effects</u> : Local
	DNEL - General population - Long term - Inhalation 33 mg/m ³ <u>Effects</u> : Systemic
	DNEL - General population - Long term - Oral 36 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 275 mg/m ³ <u>Effects</u> : Systemic
	DNEL - General population - Long term - Dermal 320 mg/kg bw/day <u>Effects</u> : Systemic

SECTION 8: Exposure controls/personal protection

	<p>DNEL - Workers - Short term - Inhalation 550 mg/m³ <u>Effects:</u> Local</p>
	<p>DNEL - Workers - Long term - Dermal 796 mg/kg bw/day <u>Effects:</u> Systemic</p>
2-methoxy-1-methylethyl acetate	<p>DNEL - Workers - Long term - Dermal 796 mg/kg bw/day <u>Effects:</u> Systemic</p> <p>DNEL - Workers - Long term - Inhalation 275 mg/m³ <u>Effects:</u> Systemic</p> <p>DNEL - Workers - Short term - Inhalation 550 mg/m³ <u>Effects:</u> Local</p> <p>DNEL - General population - Long term - Inhalation 33 mg/m³ <u>Effects:</u> Systemic</p> <p>DNEL - General population - Long term - Inhalation 33 mg/m³ <u>Effects:</u> Local</p> <p>DNEL - General population - Long term - Dermal 320 mg/kg bw/day <u>Effects:</u> Systemic</p> <p>DNEL - General population - Long term - Oral 36 mg/kg bw/day <u>Effects:</u> Systemic</p> <p>DNEL - General population - Short term - Oral 500 mg/kg bw/day <u>Effects:</u> Systemic</p>
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3	<p>DNEL - Workers - Long term - Inhalation 0.35 mg/m³ <u>Effects:</u> Systemic</p> <p>DNEL - Workers - Long term - Dermal 0.5 mg/kg <u>Effects:</u> Systemic</p> <p>DNEL - General population - Long term - Inhalation 0.085 mg/m³ <u>Effects:</u> Systemic</p> <p>DNEL - General population - Long term - Dermal 0.25 mg/kg <u>Effects:</u> Systemic</p>
Reaction mass of bis(1,2,2,6,6-pentamethyl-	<p>DNEL - Workers - Long term - Inhalation</p>

SECTION 8: Exposure controls/personal protection

4-piperidyl) sebacate and methyl
1,2,2,6,6-pentamethyl-4-piperidyl sebacate

3.53 mg/m³
Effects: Systemic

DNEL - Workers - Long term - Dermal

2 mg/kg
Effects: Systemic

DNEL - General population - Long term - Oral

0.18 mg/kg bw/day
Effects: Systemic

DNEL - General population - Long term - Inhalation

0.31 mg/m³
Effects: Systemic

DNEL - General population - Long term - Dermal

0.9 mg/kg bw/day
Effects: Systemic

DNEL - Workers - Long term - Inhalation

1.27 mg/m³
Effects: Systemic

DNEL - Workers - Long term - Dermal

1.8 mg/kg bw/day
Effects: Systemic

PNECs

Product/ingredient name

Reaction mass of ethylbenzene and xylene

Result

Fresh water

0.327 mg/l

Marine water

0.327 mg/l

Sewage Treatment Plant

6.58 mg/l

Fresh water sediment

12.46 mg/kg dwt

Marine water sediment

12.46 mg/kg dwt

Soil

2.31 mg/kg

n-butyl acetate

Soil

0.09 mg/kg

Fresh water

0.18 mg/l

Sewage Treatment Plant

35.6 mg/l

SECTION 8: Exposure controls/personal protection

	Marine water 0.018 mg/l
	Fresh water sediment 0.981 mg/kg
	Marine water sediment 0.098 mg/kg
4-methylpentan-2-one	Marine water 0.06 mg/l
	Fresh water 0.6 mg/l
	Sediment 8.27 mg/kg
2-methoxy-1-methylethyl acetate	Soil 0.29 mg/kg
	Sewage Treatment Plant 100 mg/l
	Marine water 0.064 mg/l
	Fresh water 0.635 mg/l
	Fresh water sediment 3.29 mg/kg
	Marine water sediment 0.329 mg/kg
2-methoxy-1-methylethyl acetate	Fresh water 0.635 mg/l
	Marine water 0.0635 mg/l
	Sewage Treatment Plant 100 mg/l
	Fresh water sediment 3.29 mg/kg dwt
	Marine water sediment 0.329 mg/kg dwt
	Soil 0.29 mg/kg dwt
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3	Fresh water 0.0023 mg/l

SECTION 8: Exposure controls/personal protection

Marine water

0.00023 mg/l

Sewage Treatment Plant

10 mg/l

Fresh water sediment

3.37 mg/kg

Marine water sediment

0.337 mg/kg

Soil

2 mg/kg

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Fresh water

0.0022 mg/l

Marine water

0.00022 mg/l

Secondary Poisoning

0.009 mg/l

Fresh water sediment

1.05 mg/kg

Marine water sediment

0.11 mg/kg

Soil

0.21 mg/kg

Sewage Treatment Plant

1 mg/l

8.2 Exposure controls

Appropriate engineering controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Use safety eyewear designed to protect against splash of liquids.

Skin protection

Hand protection

SECTION 8: Exposure controls/personal protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves : Duration / breakthrough time: <1 hour,
Glove material: NBR, nitrile rubber, material thickness as splash protection: at least 0.2 mm, (EN374)
Glove material: NBR, nitrile rubber Material thickness for short-term contact: at least 0.5 mm, (EN374)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

Expert judgment

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
A management program to ensure safe use including proper fitting, training on handling, duration of use, cleaning and replacement of respirators must be in place.
Recommended:
EN 140 filter mask with AXP3 or ABEK2P3 filter according to EN 14387 or pressurized air respirator according to EN 14594.
Depending on the risk assessment of the workplace, other respirator types might be selected.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Environmental exposure controls : Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Colour : Clear.
Odour : Not available.

SECTION 9: Physical and chemical properties

Odour threshold	: Not available.
Melting point/freezing point	: Technically not possible to measure
Boiling point or initial boiling point and boiling range	: 114 to 200°C
Flammability	: Not available.
Lower and upper explosion limit	: Lower: 1% Upper: 8%
Lower and upper explosive (flammable) limits	: Not available.
Flash point	: Closed cup: 14°C
Auto-ignition temperature	: 280°C
Decomposition temperature	: Not applicable.
pH	: Not applicable.
Justification	: Product is non-soluble (in water).
Viscosity	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): 15.3 mm ² /s
Vapour pressure	0.59 kPa (4.46 mm Hg)
Density	: 0.969 g/cm ³
Weight volatiles	: 53.3 % (w/w)
VOC content	: 53.3 % (w/w) (2010/75/EU)

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Further information Not available.

9.2.2 Other safety characteristics

Miscible with water : No.

Further information Not available.

room temperature (=20°C)

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly (oxyethylene) and α -3, Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result
Reaction mass of ethylbenzene and xylene	Rat - Oral - LD50 3523 to 4000 mg/kg
-	Rabbit - Dermal - LD50 121236 mg/kg
-	Rat - Inhalation - LC50 Vapour 6350 to 6700 ppm [4 hours]
Hydrocarbons, C9, aromatics	Rat - Female - Oral - LD50 3492 mg/kg OECD 401
-	Rabbit - Dermal - LD50 >3160 mg/kg OECD 402
n-butyl acetate	Rat - Oral - LD50 10768 mg/kg <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Other changes Liver - Other changes
-	Rabbit - Dermal - LD50 >17600 mg/kg
-	Rat - Inhalation - LC50 Vapour

SECTION 11: Toxicological information

	21.1 mg/l [4 hours]
4-methylpentan-2-one	Rat - Oral - LD50 2080 mg/kg
-	Rat - Inhalation - LC50 Vapour 16.4 mg/l [4 hours]
2-methoxy-1-methylethyl acetate	Rat - Oral - LD50 8532 mg/kg
-	Rabbit - Dermal - LD50 >5 g/kg
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	Rat - Male, Female - Oral - LD50 3523 mg/kg EU B.1
-	Rabbit - Male - Dermal - LD50 12126 mg/kg EU B.1
-	Rat - Male - Inhalation - LC50 Vapour 6350 ppm [4 hours] EU B.2
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rat - Male, Female - Oral - LD50 3230 mg/kg OECD [Acute Oral toxicity - Acute Toxic Class Method]
-	Rat - Male, Female - Dermal - LD50 >3170 mg/kg OECD [Acute Dermal Toxicity]

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
mixture	N/A	6190.7	N/A	41.1	N/A
Reaction mass of ethylbenzene and xylene	N/A	1100	N/A	11	N/A
Hydrocarbons, C9, aromatics	3492	N/A	N/A	N/A	N/A
n-butyl acetate	10768	N/A	N/A	21.1	N/A
4-methylpentan-2-one	2080	N/A	N/A	11	N/A
2-methoxy-1-methylethyl acetate	8532	N/A	N/A	N/A	N/A
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	3523	1100	N/A	11	N/A
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3230	N/A	N/A	N/A	N/A

Skin corrosion/irritation

SECTION 11: Toxicological information

Product/ingredient name

4-methylpentan-2-one

Result**Rabbit - Skin - Mild irritant**Duration of treatment/exposure: 24 hoursAmount/concentration applied: 500 mg

REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE

Rabbit - Skin - Irritant

EU B.4

Duration of treatment/exposure: 4 hoursObservation period: 7 days**Conclusion/Summary [Product]** : Not available.**Serious eye damage/eye irritation****Product/ingredient name**

4-methylpentan-2-one

Result**Rabbit - Eyes - Moderate irritant**Duration of treatment/exposure: 24 hoursAmount/concentration applied: 100 uL

-

Rabbit - Eyes - Severe irritantAmount/concentration applied: 40 mg**Conclusion/Summary [Product]** : Not available.**Respiratory corrosion/irritation**

Not available.

Conclusion/Summary [Product] : Not available.**Respiratory or skin sensitization**

Not available.

Skin**Conclusion/Summary [Product]** : Not available.**Respiratory****Conclusion/Summary [Product]** : Not available.**Germ cell mutagenicity**

Not available.

Conclusion/Summary [Product] : Not available.**Carcinogenicity**

Not available.

Conclusion/Summary [Product] : Not available.**Reproductive toxicity**

SECTION 11: Toxicological information

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Result
Reaction mass of ethylbenzene and xylene	STOT SE 3, H335 (Respiratory tract irritation)
-	STOT SE 3, H336 (Narcotic effects)
Hydrocarbons, C9, aromatics	STOT SE 3, H335 (Respiratory tract irritation)
-	STOT SE 3, H336 (Narcotic effects)
n-butyl acetate	STOT SE 3, H336 (Narcotic effects)
4-methylpentan-2-one	STOT SE 3, H336 (Narcotic effects)
2-methoxy-1-methylethyl acetate	STOT SE 3, H336 (Narcotic effects)
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	STOT SE 3, H335 (Respiratory tract irritation)
2-methoxy-1-methylethyl acetate	STOT SE 3, H336 (Narcotic effects)

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
Reaction mass of ethylbenzene and xylene	STOT RE 2, H373
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	STOT RE 2, H373

Aspiration hazard

Product/ingredient name	Result
Reaction mass of ethylbenzene and xylene	ASPIRATION HAZARD - Category 1
Hydrocarbons, C9, aromatics	ASPIRATION HAZARD - Category 1
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness

SECTION 11: Toxicological information

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result
Reaction mass of ethylbenzene and xylene	Acute - LC50 OECD 203 Fish - Trout - <i>Oncorhynchus mykiss</i> 2.6 mg/l [96 hours]
-	Acute - LC50 OECD 202 Daphnia - Daphnia - <i>Daphnia magna</i>

SECTION 12: Ecological information

1 mg/l [24 hours]

-	<p>Acute - EC50 OECD 201 Algae - Algae - <i>Selenastrum capricornutum</i> 2.2 mg/l [73 hours]</p>
-	<p>Chronic - NOEC OECD 301F Micro-organism - Activated sludge - <i>Activated sludge</i> 16 mg/l [28 days]</p>
Hydrocarbons, C9, aromatics	<p>Acute - LC50 OECD 203 Fish - Trout - <i>Oncorhynchus mykiss</i> 9.2 mg/l [96 hours]</p>
n-butyl acetate	<p>Acute - LC50 - Marine water Fish - Inland silverside - <i>Menidia beryllina</i> 185 ppm [96 hours] <u>Effect</u>: Mortality</p>
4-methylpentan-2-one	<p>Acute - LC50 - Fresh water Fish - Fathead minnow - <i>Pimephales promelas</i> <u>Age</u>: 29 days; <u>Size</u>: 21 mm; <u>Weight</u>: 0.141 g 505 mg/l [96 hours] <u>Effect</u>: Mortality</p>
-	<p>Chronic - NOEC - Fresh water Daphnia - Water flea - <i>Daphnia magna</i> 78 mg/l [21 days] <u>Effect</u>: Behavior</p>
-	<p>Chronic - NOEC - Fresh water Fish - Fathead minnow - <i>Pimephales promelas</i> - Embryo <u>Age</u>: <24 hours 168 mg/l [33 days] <u>Effect</u>: Mortality</p>
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	<p>Acute - LC50 Fish 2.6 mg/l [96 hours]</p>
-	<p>Acute - EC50 Daphnia 6.14 mg/l [48 hours]</p>
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3	<p>Acute - LC50 OECD 203 Fish 2.8 mg/l [96 hours]</p>
-	<p>Acute - EC50 Daphnia 4 mg/l [48 hours]</p>

SECTION 12: Ecological information

-	Acute - EC50 OECD 201 Aquatic plants >100 mg/l [72 hours]
-	Acute - EC50 Micro-organism >1000 mg/l [3 hours]
-	Chronic - NOEC OECD 202 Daphnia 0.78 mg/l [21 days]
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Acute - LC50 OECD 203, semistatic Fish - <i>Brachydanio rerio</i> 0.9 mg/l [96 hours]
-	Chronic - NOEC - Fresh water OECD [Daphnia Magna Reproduction Test] Daphnia 1 mg/l [21 days]
-	Acute - EC50 - Fresh water OECD [Alga, Growth Inhibition Test] Algae 1.68 mg/l [72 hours]

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	Result Aerobic OECD 301F 94% [28 days]
---	---

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	-	-	Readily

12.3 Bioaccumulative potential

SECTION 12: Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
Reaction mass of ethylbenzene and xylene	3.16	-	Low
n-butyl acetate	2.3	-	Low
4-methylpentan-2-one	1.9	-	Low
2-methoxy-1-methylethyl acetate	1.2	-	Low
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	-	25.9	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
n-butyl acetate	1.5	33.2139
4-methylpentan-2-one	1.6	40.9047
2-methoxy-1-methylethyl acetate	0.36	2.31363

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Reaction mass of ethylbenzene and xylene	No	No	No	No	No	No	No
Hydrocarbons, C9, aromatics	No	No	No	No	No	No	No
n-butyl acetate	No	N/A	Yes	No	N/A	N/A	Yes
4-methylpentan-2-one	No	N/A	Yes	No	N/A	N/A	Yes
2-methoxy-1-methylethyl acetate	No	N/A	Yes	No	N/A	N/A	Yes
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	N/A	N/A	N/A	Yes	N/A	N/A	N/A
2-methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly (oxyethylene) and α -3	No	No	No	No	No	No	No
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Reaction mass of ethylbenzene and xylene Hydrocarbons, C9, aromatics	N/A	N/A	N/A	Yes	N/A	N/A	N/A
n-butyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
4-methylpentan-2-one	No	N/A	N/A	No	N/A	N/A	N/A
2-methoxy-1-methylethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	No	N/A	No	Yes	No	N/A	No
2-methoxy-1-methylethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly (oxyethylene) and α -3	No	N/A	N/A	No	N/A	N/A	N/A
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Reaction mass of ethylbenzene and xylene Hydrocarbons, C9, aromatics	No	No	No	No	No	No	No
n-butyl acetate	No	No	No	No	No	No	No
4-methylpentan-2-one	No	N/A	N/A	No	N/A	N/A	N/A
2-methoxy-1-methylethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	No	N/A	No	Yes	No	N/A	No
2-methoxy-1-methylethyl acetate	No	No	No	No	No	No	No
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- ω -hydroxypoly (oxyethylene) and α -3	No	No	No	No	No	No	No
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB.
Regulation (EC) No. 1272/2008 [CLP]

SECTION 12: Ecological information

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging





Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging	European waste catalogue (EWC)
CEPE Guidelines	15 01 10* packaging containing residues of or contaminated by hazardous substances

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3 	3 	3 	3 
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	Yes.	No.	No.

Additional information

ADR/RID : **Special provisions** 640 (D)
Tunnel code (D/E)

ADN : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.
Special provisions 640 (D)

Marine pollutant : Not available.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

SECTION 15: Regulatory information

Product/ingredient name	%	Designation [Usage]
mixture	≥90	3

Labelling : Not applicable.

Other EU regulations

Explosive precursors : Not applicable.

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

National regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

Flammable liquid class (SRVFS 2005:10) : 1

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

CEPE code : 1

🔍 Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 B = Bioaccumulative
 BCF = Bioconcentration Factor
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 IATA = International Air Transport Association
 IMDG = International Maritime Dangerous Goods
 IMO = International Maritime Organization
 M = Mobile
 N/A = Not available
 P = Persistent
 PBT = Persistent, Bioaccumulative and Toxic
 PMT = Persistent, Mobile and Toxic
 PNEC = Predicted No Effect Concentration
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SGG = Segregation Group
 T = Toxic
 vB = Very Bioaccumulative

SECTION 16: Other information

vM = Very Mobile
 vP = Very Persistent
 vPvB = Very Persistent and Very Bioaccumulative
 vPvM = Very Persistent and Very Mobile

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE -

SECTION 16: Other information

Category 3

Date of issue/ Date of revision : 19 February 2026**Version** : 1.04**Date of previous issue** : 19 February 2026**Notice to reader**

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2026 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.