

## SAFETY DATA SHEET

### Section 1. Identification

**Product identifier** : UP0820

**Product name** : RAPTOR PROTECTIVE COATING - BLACK BASE

**Other means of identification** : UP0820; UP0820G; UP0822; UP4801; UP5070; UP5071; UP5072; UP5091; UP5094; UP5095; UP5096

**Date of issue** : 2/6/2026

**Version** : 6.02

**Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** : Coating component.

**Uses advised against** : Not for sale to or use by consumers.

**Supplier's details** : U-POL US Inc.  
50 Applied Bank Blvd.  
Suite 300  
Glen Mills, Pennsylvania 19342  
T (610) 746 7081  
technicalsupport@u-pol.com

**Product information** : (855) 6-AXALTA

**Emergency telephone number** : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

### Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 2  
EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
CARCINOGENICITY - Category 1A  
TOXIC TO REPRODUCTION - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

**GHS label elements**

**Hazard pictograms** :



**Signal word** :

Danger

**Hazard statements** :

H225 - Highly flammable liquid and vapor.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H350 - May cause cancer.  
H361 - Suspected of damaging fertility or the unborn child.  
H372 - Causes damage to organs through prolonged or repeated exposure.

## Section 2. Hazards identification

### Precautionary statements

<b>Prevention</b>	: P201 - Obtain special instructions before use. P280 - Wear protective gloves, protective clothing and eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 - Do not breathe vapor. P270 - Do not eat, drink or smoke when using this product.
<b>Response</b>	: P308 + P313 - IF exposed or concerned: Get medical advice or attention. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
<b>Storage</b>	: Not applicable.
<b>Disposal</b>	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Hazards not otherwise classified</b>	: None known.
<b>Hazards identified when used</b>	: <input checked="" type="checkbox"/> No known significant effects or critical hazards.

## Section 3. Composition/information on ingredients

<b>Substance/mixture</b>	: Mixture
<b>Other means of identification</b>	: UP0820; UP0820G; UP0822; UP4801; UP5070; UP5071; UP5072; UP5091; UP5094; UP5095; UP5096

Ingredient name	Synonyms	%	Identifiers
acetone	propan-2-one; propanone; 2-Propanone; Ketone propane; Dimethyl ketone; $\beta$ - ketonepropane; acetone; dimethylketone; methyl ketone; propanone; pyroacetic acid; pyroacetic ether; dimethylformaldehyde; methyl ketone; Acetone (I); 2-Propanone (I); DIMETHYLFORMALDEHYDE; 2-OXOPROPANE	$\geq 10 - \leq 30$	CAS: 67-64-1
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE		$\geq 5 - \leq 10$	CAS: --
n-butyl acetate	Acetic acid, butyl ester; Butyl Acetate; n-Butyl-acetate; Butyl ethanoate; n-Butyl ester of acetic acid; product composed of hydrocarbons (predominantly paraffinic and naphthenic) and n- butyl acetate; 1-butyl acetate; 1-Acetoxybutane; Butyl ester, Acetic acid; normal butyl acetate; Acetic acid, n-butyl ester	$\geq 1 - \leq 5$	CAS: 123-86-4

### Section 3. Composition/information on ingredients

carbon black, non respirable	Lampblack; Acetylene black; C.I. 77266; C.I. Pigment Black 6; C.I. Pigment Black 7; Charcoal	≥1 - ≤5	CAS: 1333-86-4
XYLENE	Benzene, dimethyl-; Xylol; Benzene, dimethyl-, mixed isomers; xylene, mixed isomers, pure; xylene, crude; photosensitive emulsion consisting of cyclized polyisoprene containing: — 55 % or more but not more than 75 % by weight of xylene (CAS RN 1330-20-7) and — 12 % or more but not more than 18 % by weight of ethylbenzene (CAS RN 100-41-4); Benzene, dimethyl-; Xylene (mixed); xylene (total); Xylenes; Dimethylbenzene	≥1 - ≤5	CAS: 1330-20-7
Cristobalite	Cristobalite (SiO <sub>2</sub> ); Silicon dioxide; Silica, crystalline (cristobalite); Silica, crystalline cristobalite (as quartz), respirable dust.; Silica, Crystalline Cristobalite; Silica-Crystalline, Cristobalite; Silica Crystalline - Cristobalite; Silica, crystalline - cristobalite; CRISTOBALITE DUST; CRISTOBALITE ASBESTOS; SILICA, CRISTOBALITE	≥1 - ≤5	CAS: 14464-46-1
ethylbenzene	Benzene, ethyl-; Phenylethane; Ethylbenzol; photosensitive emulsion consisting of cyclized polyisoprene containing: — 55 % or more but not more than 75 % by weight of xylene (CAS RN 1330-20-7) and — 12 % or more but not more than 18 % by weight of ethylbenzene (CAS RN 100-41-4); EB; Mono-(or di-) methyl (ethyl,bromoallyl, bromopropyl,oxycarbonyl orchloropropyl,oxycarbonyl) benzene	≥0.1 - ≤1	CAS: 100-41-4
BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATE	Decanedioic acid, 1,10-bis (1,2,2,6,6-pentamethyl-4-piperidinyl) ester; Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester; bis (1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate; Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) decanedioate; Bis	≥0.1 - ≤1	CAS: 41556-26-7

**Section 3. Composition/information on ingredients**

	<p>(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate; Bis (1,2,2,6,6-pentamethyl-4-piperidyl) decanedioate; Decanedioic acid bis (1,2,2,6,6-pentamethyl-4-piperidinyl) ester; DECANEDIOATE, BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) (PICCS); Bis(N-methyl-2,2,6,6-tetramethyl-4-piperidinyl) sebacate; Bis (1,2,2,6,6-pentamethyl-4-piperidyl) 1,8-octanedicarboxylate; DECANEDIOATE, BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL)</p>		
<p>Cristobalite</p>	<p>Cristobalite (SiO<sub>2</sub>); Silicon dioxide; Silica, crystalline (cristobalite); Silica, crystalline cristobalite (as quartz), respirable dust.; Silica, Crystalline Cristobalite; Silica-Crystalline, Cristobalite; Silica Crystalline - Cristobalite; Silica, crystalline - cristobalite; CRISTOBALITE DUST; CRISTOBALITE ASBESTOS; SILICA, CRISTOBALITE</p>	<p>≥0.1 - ≤1</p>	<p>CAS: 14464-46-1</p>
<p>methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate</p>	<p>Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidinyl) ester; Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester; methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate; methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate; Decanedioic acid methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester; Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; Methyl 1,2,2,6,6-pentamethyl-4-piperidinyl sebacate; DECANEDIOATE, METHYL, 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL; Methyl 1,2,2,6,6-pentamethyl-4-piperidyl) sebacate; Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; Decanedioic acid methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester</p>	<p>≥0.1 - ≤1</p>	<p>CAS: 82919-37-7</p>

## Section 3. Composition/information on ingredients

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

## Section 4. First aid measures

- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## Section 7. Handling and storage

**Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 5 to 30°C (41 to 86°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

**Storage code** : IA

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
acetone	<p><b>NIOSH REL (United States, 10/2020)</b> TWA 10 hours: 250 ppm. TWA 10 hours: 590 mg/m<sup>3</sup>.</p> <p><b>CAL OSHA PEL (United States, 1/2025)</b> STEL 15 minutes: 1780 mg/m<sup>3</sup>. STEL 15 minutes: 750 ppm. C: 3000 ppm. TWA 8 hours: 1200 mg/m<sup>3</sup>. TWA 8 hours: 500 ppm.</p> <p><b>OSHA PEL (United States, 5/2018)</b> TWA 8 hours: 1000 ppm. TWA 8 hours: 2400 mg/m<sup>3</sup>.</p> <p><b>OSHA PEL 1989 (United States, 3/1989)</b> TWA 8 hours: 750 ppm. TWA 8 hours: 1800 mg/m<sup>3</sup>. STEL 15 minutes: 1000 ppm. STEL 15 minutes: 2400 mg/m<sup>3</sup>.</p> <p><b>ACGIH TLV (United States, 1/2024) A4.</b> TWA 8 hours: 250 ppm. STEL 15 minutes: 500 ppm.</p>
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE n-butyl acetate	<p>None.</p> <p><b>NIOSH REL (United States, 10/2020)</b> TWA 10 hours: 150 ppm. TWA 10 hours: 710 mg/m<sup>3</sup>. STEL 15 minutes: 200 ppm. STEL 15 minutes: 950 mg/m<sup>3</sup>.</p> <p><b>CAL OSHA PEL (United States, 1/2025)</b> STEL 15 minutes: 950 mg/m<sup>3</sup>. STEL 15 minutes: 200 ppm. TWA 8 hours: 710 mg/m<sup>3</sup>. TWA 8 hours: 150 ppm.</p> <p><b>OSHA PEL (United States, 5/2018)</b> TWA 8 hours: 150 ppm. TWA 8 hours: 710 mg/m<sup>3</sup>.</p> <p><b>OSHA PEL 1989 (United States, 3/1989)</b> TWA 8 hours: 150 ppm. TWA 8 hours: 710 mg/m<sup>3</sup>.</p>

## Section 8. Exposure controls/personal protection

carbon black, non respirable

XYLENE

Cristobalite

STEL 15 minutes: 200 ppm.  
 STEL 15 minutes: 950 mg/m<sup>3</sup>.  
**ACGIH TLV (United States, 1/2024) [Butyl acetates]**  
 STEL 15 minutes: 150 ppm.  
 TWA 8 hours: 50 ppm.  
**NIOSH REL (United States, 10/2020) NIA.**  
 TWA 10 hours: 3.5 mg/m<sup>3</sup>.  
 TWA 10 hours: 0.1 mg/m<sup>3</sup> (as cyclohexane-extractable fraction).  
**CAL OSHA PEL (United States, 1/2025)**  
 TWA 8 hours: 3.5 mg/m<sup>3</sup>.  
**OSHA PEL (United States, 5/2018)**  
 TWA 8 hours: 3.5 mg/m<sup>3</sup>.  
**OSHA PEL 1989 (United States, 3/1989)**  
 TWA 8 hours: 3.5 mg/m<sup>3</sup>.  
**ACGIH TLV (United States, 1/2024) A3.**  
 TWA 8 hours: 3 mg/m<sup>3</sup>. Form: Inhalable fraction.  
**CAL OSHA PEL (United States, 1/2025) [xylene]**  
 STEL 15 minutes: 655 mg/m<sup>3</sup>.  
 STEL 15 minutes: 150 ppm.  
 C: 300 ppm.  
 TWA 8 hours: 435 mg/m<sup>3</sup>.  
 TWA 8 hours: 100 ppm.  
**OSHA PEL (United States, 5/2018) [Xylenes]**  
 TWA 8 hours: 100 ppm.  
 TWA 8 hours: 435 mg/m<sup>3</sup>.  
**OSHA PEL 1989 (United States, 3/1989) [Xylenes (o-, m-, p-isomers)]**  
 TWA 8 hours: 100 ppm.  
 TWA 8 hours: 435 mg/m<sup>3</sup>.  
 STEL 15 minutes: 150 ppm.  
 STEL 15 minutes: 655 mg/m<sup>3</sup>.  
**ACGIH TLV (United States, 1/2024) [p-xylene and mixtures containing p-xylene]**  
 A4. Ototoxicant.  
 TWA 8 hours: 20 ppm.  
**NIOSH REL (United States, 10/2020) [SILICA, CRYSTALLINE] NIA.**  
 TWA 10 hours: 0.05 mg/m<sup>3</sup>. Form: respirable dust.  
**CAL OSHA PEL (United States, 1/2025)**  
 TWA 8 hours: 0.05 mg/m<sup>3</sup>. Form: respirable dust.  
**OSHA PEL Z3 (United States, 6/2016)**  
 TWA 8 hours: 250 / 2 x (%SiO<sub>2</sub>+5) mppcf.  
 Form: Respirable.  
 TWA 8 hours: 10 / 2 x (%SiO<sub>2</sub>+2) mg/m<sup>3</sup>.  
 Form: Respirable.  
 TWA 8 hours: 30 / 2 x (%SiO<sub>2</sub>+2) mg/m<sup>3</sup>.  
 Form: Total dust.  
**OSHA PEL (United States, 5/2018) [Silica, crystalline]**

## Section 8. Exposure controls/personal protection

ethylbenzene

TWA 8 hours: 50 µg/m<sup>3</sup>. Form: Respirable dust.

**OSHA PEL 1989 (United States, 3/1989)**

TWA 8 hours: 0.05 mg/m<sup>3</sup> (as quartz). Form: Respirable dust.

**ACGIH TLV (United States, 1/2024) [Silica, crystalline] A2.**

TWA 8 hours: 0.025 mg/m<sup>3</sup>. Form: Respirable fraction.

**NIOSH REL (United States, 10/2020)**

TWA 10 hours: 100 ppm.

TWA 10 hours: 435 mg/m<sup>3</sup>.

STEL 15 minutes: 125 ppm.

STEL 15 minutes: 545 mg/m<sup>3</sup>.

**CAL OSHA PEL (United States, 1/2025)**

STEL 15 minutes: 130 mg/m<sup>3</sup>.

STEL 15 minutes: 30 ppm.

TWA 8 hours: 22 mg/m<sup>3</sup>.

TWA 8 hours: 5 ppm.

**OSHA PEL (United States, 5/2018)**

TWA 8 hours: 100 ppm.

TWA 8 hours: 435 mg/m<sup>3</sup>.

**OSHA PEL 1989 (United States, 3/1989)**

TWA 8 hours: 100 ppm.

TWA 8 hours: 435 mg/m<sup>3</sup>.

STEL 15 minutes: 125 ppm.

STEL 15 minutes: 545 mg/m<sup>3</sup>.

**ACGIH TLV (United States, 1/2024) A3.**

Ototoxicant.

TWA 8 hours: 20 ppm.

None.

**NIOSH REL (United States, 10/2020)**

**[SILICA, CRYSTALLINE] NIA.**

TWA 10 hours: 0.05 mg/m<sup>3</sup>. Form: respirable dust.

**CAL OSHA PEL (United States, 1/2025)**

TWA 8 hours: 0.05 mg/m<sup>3</sup>. Form: respirable dust.

**OSHA PEL Z3 (United States, 6/2016)**

TWA 8 hours: 250 / 2 x (%SiO<sub>2</sub>+5) mppcf.

Form: Respirable.

TWA 8 hours: 10 / 2 x (%SiO<sub>2</sub>+2) mg/m<sup>3</sup>.

Form: Respirable.

TWA 8 hours: 30 / 2 x (%SiO<sub>2</sub>+2) mg/m<sup>3</sup>.

Form: Total dust.

**OSHA PEL (United States, 5/2018) [Silica, crystalline]**

TWA 8 hours: 50 µg/m<sup>3</sup>. Form: Respirable dust.

**OSHA PEL 1989 (United States, 3/1989)**

TWA 8 hours: 0.05 mg/m<sup>3</sup> (as quartz). Form: Respirable dust.

**ACGIH TLV (United States, 1/2024) [Silica, crystalline] A2.**

TWA 8 hours: 0.025 mg/m<sup>3</sup>. Form:

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATE  
Cristobalite

## Section 8. Exposure controls/personal protection

methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Respirable fraction. None.
---	-------------------------------

### Biological exposure indices

Ingredient name	Exposure indices
acetone	<b>ACGIH BEI (United States, 1/2024)</b> BEI: 25 mg/l, acetone [in urine]. Sampling time: end of shift.
XYLENE	<b>ACGIH BEI (United States, 1/2024) [xylenes (technical or commercial grades)]</b> BEI: 0.3 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.
ethylbenzene	<b>ACGIH BEI (United States, 1/2024)</b> BEI: 150 mg/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift.

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

## Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

- Physical state** : Liquid.
- Color** : Black.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point/freezing point** : Technically not possible to measure
- Boiling point or initial boiling point and boiling range** : 56 to 141.4°C (132.8 to 286.5°F)
- Flash point** : Closed cup: -10.5°C (13.1°F)
- Evaporation rate** : Not available.
- Flammability** : Not available.
- Lower and upper explosion limit/flammability limit** : Lower: 2.1%  
Upper: 12.8%
- Vapor pressure** : 3.9 kPa (29.62 mm Hg)
- Relative vapor density** : Not available.
- Relative density** : Not available.
- Density** : 1.124 g/cm<sup>3</sup>
- Solubility(ies)** :

Media	Result
cold water	Soluble

- Solubility in water** : Not available.
- Miscible with water** : Yes.
- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : 300°C (572°F)
- Decomposition temperature** : Not applicable.
- Viscosity** : Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C (104°F)): Not available.

## Section 9. Physical and chemical properties

### Particle characteristics

**Median particle size** : Not applicable.

## Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Incompatible materials** : Reactive or incompatible with the following materials:  
oxidizing materials
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

##### **Product/ingredient name**

acetone

##### **Result**

##### **Rat - Oral - LD50**

5800 mg/kg

Toxic effects: Behavioral - Altered sleep time (including change in righting reflex) Behavioral - Tremor

##### **Rabbit - Dermal - LD50**

2001 mg/kg

##### **Rat - Inhalation - LC50 Vapor**

21 mg/l [4 hours]

REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE

##### **Rat - Male, Female - Oral - LD50**

3523 mg/kg

EU B.1

##### **Rabbit - Male - Dermal - LD50**

12126 mg/kg

EU B.1

##### **Rat - Male - Inhalation - LC50 Vapor**

6350 ppm [4 hours]

EU B.2

n-butyl acetate

##### **Rat - Oral - LD50**

10768 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Other changes Liver - Other changes

##### **Rabbit - Dermal - LD50**

>17600 mg/kg

##### **Rat - Inhalation - LC50 Vapor**

21.1 mg/l [4 hours]

## Section 11. Toxicological information

carbon black, non respirable	<b>Rat - Oral - LD50</b> >15400 mg/kg <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity)
XYLENE	<b>Rat - Oral - LD50</b> 4300 mg/kg <u>Toxic effects:</u> Liver - Other changes Kidney, Ureter, and Bladder - Other changes
ethylbenzene	<b>Rat - Inhalation - LC50 Gas.</b> 5000 ppm [4 hours] <b>Rat - Oral - LD50</b> 3500 mg/kg <u>Toxic effects:</u> Liver - Other changes Kidney, Ureter, and Bladder - Other changes <b>Rabbit - Dermal - LD50</b> >5000 mg/kg

**Conclusion/Summary [Product]** : Not available.

### Skin corrosion/irritation

#### **Product/ingredient name**

acetone

#### **Result**

##### **Rabbit - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

##### **Rabbit - Skin - Mild irritant**

Amount/concentration applied: 395 mg

##### **Rabbit - Skin - Irritant**

EU B.4

Duration of treatment/exposure: 4 hours

Observation period: 7 days

XYLENE

##### **Rat - Skin - Mild irritant**

Duration of treatment/exposure: 8 hours

Amount/concentration applied: 60 uL

##### **Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

##### **Rabbit - Skin - Moderate irritant**

Amount/concentration applied: 100 %

ethylbenzene

##### **Rabbit - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 15 mg

**Conclusion/Summary [Product]** : Not available.

### Serious eye damage/eye irritation

#### **Product/ingredient name**

#### **Result**

## Section 11. Toxicological information

acetone

**Human - Eyes - Mild irritant**

Amount/concentration applied: 186300 ppm

**Rabbit - Eyes - Mild irritant**

Amount/concentration applied: 10 uL

**Rabbit - Eyes - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

**Rabbit - Eyes - Severe irritant**

Amount/concentration applied: 20 mg

XYLENE

**Rabbit - Eyes - Mild irritant**

Amount/concentration applied: 87 mg

**Rabbit - Eyes - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

Not available.

### **Skin**

**Conclusion/Summary [Product]** : Not available.

### **Respiratory**

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Classification

## Section 11. Toxicological information

Product/ingredient name	OSHA	IARC	NTP
carbon black, non respirable	-	2B	-
XYLENE	-	3	-
Cristobalite	+	1	Known to be a human carcinogen.
ethylbenzene	-	2B	-
Cristobalite	+	1	Known to be a human carcinogen.

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Result
acetone	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
n-butyl acetate	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
XYLENE	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Cristobalite	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
ethylbenzene	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Cristobalite	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

### Aspiration hazard

Product/ingredient name	Result
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	ASPIRATION HAZARD - Category 1
XYLENE	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

### Information on the likely routes of exposure

Not available.

### Potential acute health effects

<b>Eye contact</b>	: Causes serious eye irritation.
<b>Inhalation</b>	: No known significant effects or critical hazards.
<b>Skin contact</b>	: May cause an allergic skin reaction.

## Section 11. Toxicological information

**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

**Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

#### Result

Not available.

**Conclusion/Summary [Product]** : Not available.

**General** : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : Suspected of damaging fertility or the unborn child.

### Numerical measures of toxicity

#### Acute toxicity estimates

## Section 11. Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
RAPTOR BEDLINER BLACK (OPTBLB)	39899.8	6170.4	245712.3	153.6	N/A
acetone	5800	2001	N/A	21	N/A
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	3523	1100	N/A	11	N/A
n-butyl acetate	10768	N/A	N/A	21.1	N/A
XYLENE	4300	1100	5000	N/A	N/A
ethylbenzene	3500	N/A	N/A	11	N/A

## Section 12. Ecological information

### Toxicity

#### Product/ingredient name

acetone

#### Result

##### Acute - LC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*

10 mg/l [48 hours]

Effect: Mortality

##### Chronic - NOEC - Marine water

Algae - Green algae - *Ulva pertusa*

4.95 mg/l [96 hours]

Effect: Reproduction

##### Acute - EC50 - Marine water

Algae - Green algae - *Ulva pertusa*

20.565 mg/l [96 hours]

Effect: Reproduction

##### Chronic - NOEC - Fresh water

Crustaceans - Daphnia - *Daphniidae*

0.016 ml/l [21 days]

Effect: Population

##### Acute - LC50 - Fresh water

Fish - Guppy - *Poecilia reticulata*

Age: 4 to 12 months; Size: 2 to 10 cm; Weight: 0.5 to 14 g

5600 ppm [96 hours]

Effect: Mortality

REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE

##### Acute - LC50

Fish

2.6 mg/l [96 hours]

##### Acute - EC50

Daphnia

6.14 mg/l [48 hours]

n-butyl acetate

##### Acute - LC50 - Marine water

Fish - Inland silverside - *Menidia beryllina*

185 ppm [96 hours]

Effect: Mortality

XYLENE

##### Acute - LC50 - Fresh water

Fish - Fathead minnow - *Pimephales promelas*

Age: 31 days; Size: 18.4 mm; Weight: 0.077 g

13.4 mg/l [96 hours]

Effect: Mortality

##### EC50

## Section 12. Ecological information

ethylbenzene

Crustaceans - *Penaeus monodon*

3.82 mg/l [48 hours]

**Acute - LC50 - Marine water**Crustaceans - Brine shrimp - *Artemia sp.* - Nauplii

Age: 2 to 3

13.3 mg/l [48 hours]

Effect: Mortality

**Acute - EC50 - Fresh water**Algae - Green algae - *Raphidocelis subcapitata*

3600 µg/l [96 hours]

Effect: Population

**Conclusion/Summary [Product]** : Not available.

### Persistence and degradability

Product/ingredient name

Result

 REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE
**Aerobic**

OECD 301F

94% [28 days]

XYLENE

OECD 301 F

90% [28 days]

**Conclusion/Summary [Product]** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
<input checked="" type="checkbox"/> REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	-	-	Readily
XYLENE	-	-	Readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
<input checked="" type="checkbox"/> acetone	-0.23	-	Low
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	-	25.9	Low
n-butyl acetate	2.3	-	Low
XYLENE	3.12	8.1 to 25.9	Low
ethylbenzene	3.6	-	Low

### Mobility in soil

**Soil/Water partition coefficient** : Not available.

### Other adverse effects

No known significant effects or critical hazards.






## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Acetone (l) Xylene	67-64-1 1330-20-7	Listed Listed	U002 U239

## Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3 	3 	3 	3 
Packing group	II	II	II	II	II
Environmental hazards	No.	No.	No.	No.	No.

### Additional information

**DOT Classification** : **Reportable quantity** 4914.2 lbs / 2231.1 kg [524.36 gal / 1984.9 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

**TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

## Section 14. Transport information

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

## Section 15. Regulatory information

### U.S. Federal regulations

**TSCA 8(a) PAIR:** 2-methoxy-1-methylethyl acetate; octamethylcyclotetrasiloxane; decamethylcyclopentasiloxane; dodecamethylcyclohexasiloxane

**TSCA 8(a) CDR Exempt/Partial exemption:** Not determined

**Clean Water Act (CWA) 307:** ethylbenzene; toluene

**Clean Water Act (CWA) 311:** n-butyl acetate; XYLENE ; ethylbenzene; toluene

### TSCA 12(b) - Chemical export notification

Not applicable.

**Clean Air Act Section 112** : Listed

**(b) Hazardous Air Pollutants (HAPs)**

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : FLAMMABLE LIQUIDS - Category 2  
EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
CARCINOGENICITY - Category 1A  
TOXIC TO REPRODUCTION - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

#### Composition/information on ingredients

Name	%	Classification
acetone	≥10 - ≤30	FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
REACTION MASS OF ETHYLBENZENE, M-XYLENE AND PXYLENE	≥5 - ≤10	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

## Section 15. Regulatory information

n-butyl acetate	≥1 - ≤5	(Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
carbon black, non respirable XYLENE	≥1 - ≤5 ≥1 - ≤5	CARCINOGENICITY - Category 2 FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
Cristobalite	≥1 - ≤5	ASPIRATION HAZARD - Category 1 CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
ethylbenzene	≥0.1 - ≤1	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATE	≥0.1 - ≤1	ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 4 SKIN SENSITIZATION - Category 1A TOXIC TO REPRODUCTION - Category 2
Cristobalite	≥0.1 - ≤1	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	≥0.1 - ≤1	FLAMMABLE LIQUIDS - Category 4 SKIN SENSITIZATION - Category 1A TOXIC TO REPRODUCTION - Category 2

### SARA 313

	Product name	CAS number	%
<b>Form R - Reporting requirements</b>	XYLENE	1330-20-7	≥1 - ≤5
	ethylbenzene	100-41-4	≥0.1 - ≤1
<b>Supplier notification</b>	XYLENE	1330-20-7	≥1 - ≤5
	ethylbenzene	100-41-4	≥0.1 - ≤1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

- Massachusetts** : The following components are listed: ACETONE; BUTYL ACETATE; CARBON BLACK; XYLENE; CRISTOBALITE DUST
- New York** : The following components are listed: Acetone; Butyl acetate; Xylene mixed
- New Jersey** : The following components are listed: ACETONE; n-BUTYL ACETATE; CARBON BLACK; XYLENES; SILICA, CRISTOBALITE; DIMETHYL SULFOXIDE; ETHYL BENZENE; SILICA, CRISTOBALITE
- Pennsylvania** : The following components are listed: 2-PROPANONE; ACETIC ACID, BUTYL ESTER; CARBON BLACK; BENZENE, DIMETHYL-; CRISTOBALITE DUST; SILICA AMORPHOUS DIATOMACEOUS EARTH (UNCALCINED)

## Section 15. Regulatory information

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

**Canada** : All components are listed or exempted.

**United States** : All components are listed or exempted.

## Section 16. Other information


### Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### National Fire Protection Association (U.S.A.)



### History

**Date of issue** : 2/6/2026

**Version** : 6.02

Product stewardship and regulatory compliance.

### Key to abbreviations

: ATE = Acute Toxicity Estimate  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL = International Convention for the Prevention From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

## Section 16. Other information

UN = United Nations

▣ Indicates information that has changed from previously issued version.

### Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2026 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.