

## SAFETY DATA SHEET

### Section 1. Identification

**Product identifier** : RCEBAL  
**Product name** : RAPTOR CALIPER ENAMEL SATIN BLACK  
**Other means of identification** : RCEB/AL  
**Date of issue** : 21 April 2026  
**Version** : 3.02

#### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** : Coating component.  
**Uses advised against** : Not for sale to or use by consumers.

**Supplier's details** : U-POL AUSTRALIA PTY LTD.  
16 DARLING ST, MARSDEN PARK NSW 2765 AUSTRALIA.  
TEL: 02 4731 2655  
EMAIL: INFO@U-POL.COM.AU  
WEB: WWW.U-POL.COM.AU  
A.C.N. 633 592 819

U-POL NZ Ltd,  
C/O LINDSAY & ASSOCIATES,  
UNIT H, 12 AMERA PLACE, EAST TAMAKI, AUCKLAND  
TEL: 027 630 3691  
Email: Info@u-pol.co.nz  
Tech Support: technicalsupport@u-pol.com  
Web: www.u-pol.co.nz

**Product information** : (855) 6-AXALTA

**Emergency telephone number** : Australia (CHEMTREC): + (61) - 290372994

### Section 2. Hazard(s) identification


Classified as **HAZARDOUS** according to the GHS criteria under Australian Work Health Safety (WHS) Act 2011.

Classified as **DANGEROUS GOODS** according to the Australian Dangerous Goods (ADG).

**Classification of the substance or mixture** : AEROSOLS - Category 1  
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A  
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3

#### GHS label elements

**Hazard pictograms** :



**Signal word** : **DANGER**

## Section 2. Hazard(s) identification

**Hazard statements** : H222, H229 - Extremely flammable aerosol. Pressurised container: may burst if heated.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.

### Precautionary statements

**Prevention** : P280 - Wear eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P261 - Avoid breathing dust or mist.  
P251 - Do not pierce or burn, even after use.

**Response** : P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice or attention.

**Storage** : P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label elements** : Not applicable.

**Other hazards which do not result in classification** : None known.

## Section 3. Composition and ingredient information

**Substance/mixture** : Mixture

Ingredient name	% (w/w)	CAS number
dimethyl ether	30 - <60	115-10-6
methyl acetate	30 - <60	79-20-9
n-butyl acetate	5 - <10	123-86-4
xylene	3 - <5	1330-20-7
2-methoxy-1-methylethyl acetate	1 - <3	108-65-6

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.**

**The total concentration of ingredients in this product, reported or not in this section, is 100%.**

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First aid measures

### Description of necessary first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

## Section 4. First aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### **Most important symptoms/effects, acute and delayed**

#### **Potential acute health effects**

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression.

#### **Over-exposure signs/symptoms**

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### **Indication of immediate medical attention and special treatment needed, if necessary**

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Firefighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

**Specific hazards arising from the chemical** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

## Section 6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls and personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
dimethyl ether	<b>Safe Work Australia (Australia, 1/2024)</b> TWA 8 hours: 400 ppm. TWA 8 hours: 760 mg/m <sup>3</sup> . STEL 15 minutes: 500 ppm. STEL 15 minutes: 950 mg/m <sup>3</sup> .
methyl acetate	<b>Safe Work Australia (Australia, 1/2024)</b> STEL 15 minutes: 757 mg/m <sup>3</sup> . STEL 15 minutes: 250 ppm. TWA 8 hours: 606 mg/m <sup>3</sup> . TWA 8 hours: 200 ppm.
n-butyl acetate	<b>Safe Work Australia (Australia, 1/2024)</b> STEL 15 minutes: 950 mg/m <sup>3</sup> .



## Section 8. Exposure controls and personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid.
- Colour** : Black.
- Odour** : Characteristic.
- Odour threshold** : Not available.
- pH** : Not applicable.
- Melting point** : Technically not possible to measure
- Boiling point** : Not applicable.
- Flash point** : Closed cup: -41°C (-41.8°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Lower: 1.2%  
Upper: 26.2%
- Vapour pressure** : 232.7 kPa (1745.05 mm Hg)
- Vapour density** : Not available.
- Density** : 0.802 g/cm<sup>3</sup>
- Solubility(ies)** :  
Not available.
- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : 333°C (631.4°F)
- Decomposition temperature** : Not applicable.
- Viscosity** : Dynamic (room temperature): Not available.  
Kinematic (room temperature): Not available.  
Kinematic (40°C (104°F)): Not available.
- Flow time (ISO 2431)** : Not available.

### Aerosol product

- Type of aerosol** : Spray
- Heat of combustion** : 24.92 kJ/g

## Section 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame).
<b>Incompatible materials</b>	: No specific data.
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result
dimethyl ether	<b>Rat - Oral - LD50</b> >99999 mg/kg
-	<b>Rat - Dermal - LD50</b> >99999 mg/kg
-	<b>Rat - Inhalation - LC50 Vapour</b> 309 g/m <sup>3</sup> [4 hours]
-	<b>Rat - Inhalation - LC50 Gas.</b> 164000 ppm [4 hours] <u>Toxic effects:</u> Behavioral - Ataxia Behavioral - Coma
methyl acetate	<b>Rat - Oral - LD50</b> >5 g/kg
-	<b>Rabbit - Dermal - LD50</b> >5 g/kg
n-butyl acetate	<b>Rat - Oral - LD50</b> 10768 mg/kg <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Other changes Liver - Other changes
-	<b>Rabbit - Dermal - LD50</b> >17600 mg/kg
-	<b>Rat - Inhalation - LC50 Vapour</b> 21.1 mg/l [4 hours]
xylene	<b>Rat - Oral - LD50</b> 4300 mg/kg <u>Toxic effects:</u> Liver - Other changes Kidney, Ureter, and Bladder - Other changes
-	<b>Rat - Inhalation - LC50 Gas.</b> 5000 ppm [4 hours]
2-methoxy-1-methylethyl acetate	<b>Rat - Oral - LD50</b> 8532 mg/kg
-	<b>Rabbit - Dermal - LD50</b> >5 g/kg

## Section 11. Toxicological information

### Skin corrosion/irritation

#### Product/ingredient name

methyl acetate

-

xylene

-

-

#### Result

##### **Rabbit - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

##### **Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

##### **Rat - Skin - Mild irritant**

Duration of treatment/exposure: 8 hours

Amount/concentration applied: 60 uL

##### **Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

##### **Rabbit - Skin - Moderate irritant**

Amount/concentration applied: 100 %

### Serious eye damage/eye irritation

#### Product/ingredient name

methyl acetate

xylene

-

#### Result

##### **Rabbit - Eyes - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

##### **Rabbit - Eyes - Mild irritant**

Amount/concentration applied: 87 mg

##### **Rabbit - Eyes - Severe irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 5 mg

### Respiratory corrosion/irritation

Not available.

### Respiratory or skin sensitization

Not available.

### Germ cell mutagenicity

Not available.

### Carcinogenicity

Not available.

### Reproductive toxicity

Not available.

### Specific target organ toxicity (single exposure)

#### Product/ingredient name

#### Result

## Section 11. Toxicological information

methyl acetate	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3
n-butyl acetate	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3
xylene	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1

### Information on likely routes of exposure

Not available.

### Potential acute health effects

<b>Eye contact</b>	: Causes serious eye irritation.
<b>Inhalation</b>	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
<b>Skin contact</b>	: No known significant effects or critical hazards.
<b>Ingestion</b>	: Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Eye contact</b>	: Adverse symptoms may include the following: pain or irritation watering redness
<b>Inhalation</b>	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
<b>Skin contact</b>	: No specific data.
<b>Ingestion</b>	: No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

<b>Potential immediate effects</b>	: Not available.
<b>Potential delayed effects</b>	: Not available.

#### Long term exposure

<b>Potential immediate effects</b>	: Not available.
------------------------------------	------------------

## Section 11. Toxicological information

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**General** : No known significant effects or critical hazards.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### **Acute toxicity estimates**

Route	ATE value
Dermal	30392.87 mg/kg
Inhalation (gases)	138149.42 ppm

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result
methyl acetate	<b>Acute - LC50 - Fresh water</b> Fish - Fathead minnow - <i>Pimephales promelas</i> Age: 28 to 32 days; Size: 17.5 mm; Weight: 0.087 g 320 mg/l [96 hours] Effect: Mortality
n-butyl acetate	<b>Acute - LC50 - Marine water</b> Fish - Inland silverside - <i>Menidia beryllina</i> 185 ppm [96 hours] Effect: Mortality
xylene	<b>Acute - LC50 - Fresh water</b> Fish - Fathead minnow - <i>Pimephales promelas</i> Age: 31 days; Size: 18.4 mm; Weight: 0.077 g 13.4 mg/l [96 hours] Effect: Mortality
-	<b>EC50</b> Crustaceans - <i>Penaeus monodon</i> 3.82 mg/l [48 hours]

### Persistence and degradability

Product/ingredient name	Result
xylene	OECD 301 F 90% [28 days]

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily

### Bioaccumulative potential

## Section 12. Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
dimethyl ether	0.07	-	Low
methyl acetate	0.18	-	Low
n-butyl acetate	2.3	-	Low
xylene	3.12	8.1 to 25.9	Low
2-methoxy-1-methylethyl acetate	1.2	-	Low

### Mobility in soil

**Soil/water partition coefficient** : Not available.




### Other adverse effects

No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## Section 14. Transport information

	ADG	IMDG	IATA
<b>UN number</b>	UN1950	UN1950	UN1950
<b>UN proper shipping name</b>	AEROSOLS	AEROSOLS	Aerosols, flammable
<b>Transport hazard class(es)</b>	2.1 	2.1 	2.1 
<b>Packing group</b>	-	-	-
<b>Environmental hazards</b>	No.	No.	No.

### Additional information

**Hazchem code** : Not available.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## Section 14. Transport information

**Transport in bulk according to IMO instruments** : Not available.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

## Section 15. Regulatory information

### Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

## Section 16. Any other relevant information

### History

**Date of issue** : 21 April 2026

**Key to abbreviations** :

- ACGIH = Association Advancing Occupational and Environmental Health
- ADG = Australian Dangerous Goods
- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- DFG = Deutsche Forschungsgemeinschaft, German research funding organization
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MAK value = Maximum Permissible Concentration
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- STEL = Short-Term Exposure Limit
- TLV = Threshold Limit Value
- TWA = Time-Weighted Average

▣ Indicates information that has changed from previously issued version.

### Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

**Section 16. Any other relevant information**

© 2026 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.