

# SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product identifier** : ECOATW/AL  
**Product name** : E-COAT REPAIR 12 WHITE AEROSOL  
**Product type** : Aerosol.  
**Other means of identification** : Not available.  
**Date of issue/ Date of revision** : 19 February 2026  
**Version** : 1.01  
**Date of previous issue** : 5 March 2025

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** : Coating component.  
**Uses advised against** : Not for sale to or use by consumers.

### 1.3 Details of the supplier of the safety data sheet

U-POL LTD,  
DENINGTON ROAD,  
WELLINGBOROUGH,  
NN8 2QH  
+44 (0) 1933 230310  
sds-competence@axalta.com

**e-mail address of person responsible for this SDS** : sds-competence@axalta.com

U-POL NETHERLANDS B.V,  
DE GEER 14,  
4004LT TIEL,  
NETHERLANDS  
+31 20 240 2216  
sds-competence@axalta.com

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** : +(44)-870-8200418

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to UK CLP/GHS

Aerosol 1, H222, H229  
Eye Irrit. 2, H319  
Skin Sens. 1, H317  
STOT SE 3, H336


**SECTION 2: Hazards identification**

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

**Ingredients of unknown toxicity** : 14 percent of the mixture consists of component(s) of unknown acute inhalation toxicity

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

**2.2 Label elements****Hazard pictograms****Signal word**

: Danger

**Contains**

: methyl acetate  
n-butyl acetate  
Fatty acids, C14-18 and C16-18-unsatd., maleated  
reaction mass of  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)  
propionyl- $\omega$ -hydroxypoly(oxyethylene) and  $\alpha$ -3  
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl  
1,2,2,6,6-pentamethyl-4-piperidyl sebacate  
maleic anhydride

**Hazard statements**

: H222, H229 - Extremely flammable aerosol. Pressurised container: may burst if heated.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.

**Precautionary statements****Prevention**

: P280 - Wear protective gloves. Wear eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.

**Response**

: P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Storage**

: P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**Disposal**

: Not applicable.

**Supplemental label elements**

: EUH066 - Repeated exposure may cause skin dryness or cracking.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

: Not applicable.

**2.3 Other hazards****Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII**

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification**

: None known.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
dimethyl ether	REACH #: 01-2119472128-37 EC: 204-065-8 CAS: 115-10-6 Index: 603-019-00-8	≥25 - ≤50	Flam. Gas 1A, H220 Press. Gas (Comp.), H280	[1] [2]
methyl acetate	REACH #: 01-2119459211-47 EC: 201-185-2 CAS: 79-20-9 Index: 607-021-00-X	≥10 - ≤25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[1] [2]
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4	≥10 - ≤25	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[1] [2]
butanone	REACH #: 01-2119457290-43 EC: 201-159-0 CAS: 78-93-3	≥10 - ≤25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[1] [2]
2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6	≤5	Flam. Liq. 3, H226 STOT SE 3, H336	[1] [2]
Reaction mass of ethylbenzene and xylene	REACH #: 01-2119539452-40 EC: 905-588-0	≤3	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	[1]
Fatty acids, C14-18 and C16-18-unsatd., maleated	EC: 288-306-2 CAS: 85711-46-2	<1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317	[1]
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3	REACH #: 01-0000015075-76 EC: 400-830-7	≤0.3	Skin Sens. 1A, H317 Aquatic Chronic 2, H411	[1]
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≤0.19	Skin Sens. 1A, H317 Repr. 2, H361 (oral) Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
maleic anhydride	REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9	≤0.1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (inhalation) EUH071  <b>See Section 16 for the full text of the H statements declared above.</b>	[1] [2]

### SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a physical, health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
 pain or irritation  
 watering  
 redness
- Inhalation** : Adverse symptoms may include the following:  
 respiratory tract irritation  
 coughing  
 nausea or vomiting  
 headache  
 drowsiness/fatigue  
 dizziness/vertigo  
 unconsciousness

## SECTION 4: First aid measures

- Skin contact** : Adverse symptoms may include the following:  
 irritation  
 redness  
 dryness  
 cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
 See Section 8 for information on appropriate personal protective equipment.  
 See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.  
 In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.  
 Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.  
 Keep away from heat, sparks and flame. No sparking tools should be used.  
 Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.  
 Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.  
 Put on appropriate personal protective equipment (see Section 8).  
 Never use pressure to empty. Container is not a pressure vessel.  
 Always keep in containers made from the same material as the original one.  
 Comply with the health and safety at work laws.  
 Do not allow to enter drains or watercourses.

#### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P3a	150 tonnes	500 tonnes

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

 dimethyl ether

#### EH40/2005 WELs (United Kingdom (UK), 1/2020)

STEL 15 minutes: 958 mg/m<sup>3</sup>.  
 STEL 15 minutes: 500 ppm.  
 TWA 8 hours: 400 ppm.  
 TWA 8 hours: 766 mg/m<sup>3</sup>.

methyl acetate

#### EH40/2005 WELs (United Kingdom (UK), 1/2020)

STEL 15 minutes: 770 mg/m<sup>3</sup>.  
 STEL 15 minutes: 250 ppm.  
 TWA 8 hours: 616 mg/m<sup>3</sup>.  
 TWA 8 hours: 200 ppm.

n-butyl acetate

#### EH40/2005 WELs (United Kingdom (UK), 1/2020)

STEL 15 minutes: 966 mg/m<sup>3</sup>.  
 STEL 15 minutes: 200 ppm.

## SECTION 8: Exposure controls/personal protection

butanone	<p>TWA 8 hours: 724 mg/m<sup>3</sup>. TWA 8 hours: 150 ppm. <b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b> Absorbed through skin. STEL 15 minutes: 899 mg/m<sup>3</sup>. STEL 15 minutes: 300 ppm. TWA 8 hours: 600 mg/m<sup>3</sup>. TWA 8 hours: 200 ppm.</p>
2-methoxy-1-methylethyl acetate	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b> Absorbed through skin. STEL 15 minutes: 548 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. TWA 8 hours: 274 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm.</p>
maleic anhydride	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b> Inhalation sensitiser. STEL 15 minutes: 3 mg/m<sup>3</sup>. TWA 8 hours: 1 mg/m<sup>3</sup>.</p>

### Biological exposure indices

Product/ingredient name	Exposure indices
butanone	<b>EH40/2005 BMGVs (United Kingdom (UK), 1/2020)</b> BGV: 70 µmol/l, butan-2-one [in urine]. Sampling time: post shift.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

#### Product/ingredient name

dimethyl ether

#### Result

**DNEL - General population - Long term - Inhalation**  
471 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - Workers - Long term - Inhalation**  
1894 mg/m<sup>3</sup>  
Effects: Systemic

methyl acetate

**DNEL - General population - Long term - Oral**  
21.5 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Long term - Dermal**  
21.5 mg/kg bw/day  
Effects: Systemic

**DNEL - Workers - Long term - Dermal**  
43 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Long term - Inhalation**  
64 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - General population - Long term - Inhalation**  
133 mg/m<sup>3</sup>  
Effects: Local

## SECTION 8: Exposure controls/personal protection

**DNEL - General population - Short term - Oral**

203 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Short term - Dermal**

203 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

300 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

620 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Short term - Inhalation**

3777 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation**

3777 mg/m<sup>3</sup>

Effects: Systemic

n-butyl acetate

**DNEL - Workers - Short term - Dermal**

11 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Oral**

2 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Short term - Oral**

2 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Dermal**

3.4 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Short term - Dermal**

6 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Short term - Dermal**

11 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Inhalation**

12 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Long term - Inhalation**

35.7 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Short term - Inhalation**

300 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Short term - Inhalation**

300 mg/m<sup>3</sup>

Effects: Systemic

**SECTION 8: Exposure controls/personal protection**

**DNEL - Workers - Long term - Inhalation**

300 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Short term - Inhalation**

600 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Short term - Inhalation**

600 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

300 mg/m<sup>3</sup>

Effects: Systemic

butanone

**DNEL - Workers - Long term - Inhalation**

200.539 ppm

Effects: Systemic

**DNEL - General population - Long term - Oral**

31 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Inhalation**

106 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Long term - Dermal**

412 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Short term - Inhalation**

450 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

600 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation**

900 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Dermal**

1161 mg/kg bw/day

Effects: Systemic

2-methoxy-1-methylethyl acetate

**DNEL - Workers - Long term - Dermal**

796 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

275 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation**

550 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Long term - Inhalation**

33 mg/m<sup>3</sup>

Effects: Systemic

## SECTION 8: Exposure controls/personal protection

### **DNEL - General population - Long term - Inhalation**

33 mg/m<sup>3</sup>

Effects: Local

### **DNEL - General population - Long term - Dermal**

320 mg/kg bw/day

Effects: Systemic

### **DNEL - General population - Long term - Oral**

36 mg/kg bw/day

Effects: Systemic

### **DNEL - General population - Short term - Oral**

500 mg/kg bw/day

Effects: Systemic

Reaction mass of ethylbenzene and xylene

### **DNEL - Workers - Long term - Dermal**

212 mg/kg bw/day

Effects: Systemic

### **DNEL - Workers - Long term - Inhalation**

221 mg/m<sup>3</sup>

Effects: Systemic

Fatty acids, C14-18 and C16-18-unsatd.,  
maleated

### **DNEL - General population - Long term - Oral**

1.5 mg/kg bw/day

Effects: Systemic

### **DNEL - General population - Long term - Dermal**

1.5 mg/kg bw/day

Effects: Systemic

### **DNEL - Workers - Long term - Dermal**

3 mg/kg bw/day

Effects: Systemic

reaction mass of  $\alpha$ -3-(3-(2H-benzotriazol-  
2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-  
 $\omega$ -hydroxypoly(oxyethylene) and  $\alpha$ -3

### **DNEL - Workers - Long term - Inhalation**

0.35 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - Workers - Long term - Dermal**

0.5 mg/kg

Effects: Systemic

### **DNEL - General population - Long term - Inhalation**

0.085 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - General population - Long term - Dermal**

0.25 mg/kg

Effects: Systemic

Reaction mass of bis(1,2,2,6,6-pentamethyl-  
4-piperidyl) sebacate and methyl  
1,2,2,6,6-pentamethyl-4-piperidyl sebacate

### **DNEL - Workers - Long term - Inhalation**

3.53 mg/m<sup>3</sup>

Effects: Systemic

### **DNEL - Workers - Long term - Dermal**

2 mg/kg

Effects: Systemic

### **DNEL - General population - Long term - Oral**

0.18 mg/kg bw/day

Effects: Systemic

## SECTION 8: Exposure controls/personal protection

maleic anhydride

**DNEL - General population - Long term - Inhalation**  
 0.31 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - General population - Long term - Dermal**  
 0.9 mg/kg bw/day  
Effects: Systemic

**DNEL - Workers - Long term - Inhalation**  
 1.27 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - Workers - Long term - Dermal**  
 1.8 mg/kg bw/day  
Effects: Systemic

**DNEL - Workers - Short term - Dermal**  
 0.04 mg/kg  
Effects: Systemic

**DNEL - Workers - Long term - Inhalation**  
 0.4 mg/cm<sup>2</sup>  
Effects: Systemic

**DNEL - General population - Long term - Inhalation**  
 0.05 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - General population - Long term - Oral**  
 0.06 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Long term - Inhalation**  
 0.08 mg/m<sup>3</sup>  
Effects: Local

**DNEL - Workers - Long term - Inhalation**  
 0.081 mg/m<sup>3</sup>  
Effects: Local

**DNEL - Workers - Long term - Inhalation**  
 0.081 mg/m<sup>3</sup>  
Effects: Systemic

**DNEL - General population - Short term - Oral**  
 0.1 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Short term - Dermal**  
 0.1 mg/kg bw/day  
Effects: Systemic

**DNEL - General population - Long term - Dermal**  
 0.1 mg/kg bw/day  
Effects: Systemic

**DNEL - Workers - Short term - Dermal**  
 0.2 mg/kg bw/day  
Effects: Systemic

**DNEL - Workers - Long term - Dermal**  
 0.2 mg/kg bw/day  
Effects: Systemic

**SECTION 8: Exposure controls/personal protection**

**DNEL - Workers - Short term - Inhalation**

0.2 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Short term - Inhalation**

0.2 mg/m<sup>3</sup>

Effects: Systemic

**PNECs**

**Product/ingredient name**

butyl acetate

**Result**

**Soil**

0.09 mg/kg

**Fresh water**

0.18 mg/l

**Sewage Treatment Plant**

35.6 mg/l

**Marine water**

0.018 mg/l

**Fresh water sediment**

0.981 mg/kg

**Marine water sediment**

0.098 mg/kg

butanone

**Fresh water**

55.8 mg/l

**Sewage Treatment Plant**

709 mg/l

**Fresh water sediment**

284.7 mg/kg

**Marine water sediment**

284.7 mg/kg

**Marine water**

55.8 mg/l

**Sewage Treatment Plant**

22.5 mg/kg

2-methoxy-1-methylethyl acetate

**Fresh water**

0.635 mg/l

**Marine water**

0.0635 mg/l

**Sewage Treatment Plant**

100 mg/l

**Fresh water sediment**

3.29 mg/kg dwt

**Marine water sediment**

0.329 mg/kg dwt

**Soil**

0.29 mg/kg dwt

## SECTION 8: Exposure controls/personal protection

Reaction mass of ethylbenzene and xylene

**Fresh water**

0.327 mg/l

**Marine water**

0.327 mg/l

**Sewage Treatment Plant**

6.58 mg/l

**Fresh water sediment**

12.46 mg/kg dwt

**Marine water sediment**

12.46 mg/kg dwt

**Soil**

2.31 mg/kg

reaction mass of  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and  $\alpha$ -3

**Fresh water**

0.0023 mg/l

**Marine water**

0.00023 mg/l

**Sewage Treatment Plant**

10 mg/l

**Fresh water sediment**

3.37 mg/kg

**Marine water sediment**

0.337 mg/kg

**Soil**

2 mg/kg

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

**Fresh water**

0.0022 mg/l

**Marine water**

0.00022 mg/l

**Secondary Poisoning**

0.009 mg/l

**Fresh water sediment**

1.05 mg/kg

**Marine water sediment**

0.11 mg/kg

**Soil**

0.21 mg/kg

**Sewage Treatment Plant**

1 mg/l

maleic anhydride

**Marine water**

0.004281 mg/l

**Fresh water**

0.04281 mg/l

## SECTION 8: Exposure controls/personal protection

**Sediment**  
0.334 mg/l

### 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Use safety eyewear designed to protect against splash of liquids.

#### Skin protection

##### **Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : Duration / breakthrough time: <1 hour,  
Glove material: NBR, nitrile rubber, material thickness as splash protection: at least 0.2 mm, (EN374)  
Glove material: NBR, nitrile rubber Material thickness for short-term contact: at least 0.5 mm, (EN374)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

Expert judgment

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.  
A management program to ensure safe use including proper fitting, training on handling, duration of use, cleaning and replacement of respirators must be in place.  
Recommended:  
EN 140 filter mask with AXP3 or ABEK2P3 filter according to EN 14387 or pressurized air respirator according to EN 14594.  
Depending on the risk assessment of the workplace, other respirator types might be selected.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If

**SECTION 8: Exposure controls/personal protection**

exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

**SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**9.1 Information on basic physical and chemical properties****Appearance**

<b>Physical state</b>	: Liquid.
<b>Colour</b>	: White.
<b>Odour</b>	: Not available.
<b>Odour threshold</b>	: Not available.
<b>Melting point/freezing point</b>	: Technically not possible to measure
<b>Initial boiling point and boiling range</b>	: Not applicable.
<b>Flammability (solid, gas)</b>	: Not available.
<b>Upper/lower flammability or explosive limits</b>	: Lower: 1% Upper: 26.2% Not available.
<b>Flash point</b>	: Closed cup: -41°C (-41.8°F)
<b>Auto-ignition temperature</b>	: 333°C (631.4°F)
<b>Decomposition temperature</b>	: Not applicable.
<b>pH</b>	: Not applicable.
<b>Viscosity</b>	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): Not available.
<b>Solubility in water</b>	: Not available.
<b>Miscible with water</b>	: Yes.
<b>Partition coefficient: n-octanol/ water</b>	: Not applicable.
<b>Vapour pressure</b>	: 199.5 kPa (1496 mm Hg)
<b>Relative density</b>	: Not available.
<b>Density</b>	: 0.819 g/cm <sup>3</sup>
<b>Vapour density</b>	: Not available.
<b>Explosive properties</b>	: Not available.
<b>Oxidising properties</b>	: Not available.
<b>Weight volatiles</b>	: 83.4 % (w/w)
<b>VOC content</b>	: 83.3 % (w/w) (2010/75/EU)

**9.2 Other information****9.2.1 Information with regard to physical hazard classes**

**Heat of combustion** : 23.26 kJ/g

**Aerosol product**

**Type of aerosol** : Spray

Further information Not available.

**9.2.2 Other safety characteristics**

**Miscible with water** : Yes.

E-COAT REPAIR 12 WHITE AEROSOL

## SECTION 9: Physical and chemical properties

Further information Not available.

*room temperature (=20°C)*

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result
dimethyl ether	<p><b>Rat - Oral - LD50</b> &gt;99999 mg/kg</p> <p><b>Rat - Dermal - LD50</b> &gt;99999 mg/kg</p> <p><b>Rat - Inhalation - LC50 Vapour</b> 309 g/m<sup>3</sup> [4 hours]</p> <p><b>Rat - Inhalation - LC50 Gas.</b> 164000 ppm [4 hours] <u>Toxic effects:</u> Behavioral - Ataxia Behavioral - Coma</p>
methyl acetate	<p><b>Rat - Oral - LD50</b> &gt;5 g/kg</p> <p><b>Rabbit - Dermal - LD50</b> &gt;5 g/kg</p>
n-butyl acetate	<p><b>Rat - Oral - LD50</b> 10768 mg/kg <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) Lung, Thorax, or Respiration - Other changes Liver - Other changes</p> <p><b>Rabbit - Dermal - LD50</b> &gt;17600 mg/kg</p> <p><b>Rat - Inhalation - LC50 Vapour</b> 21.1 mg/l [4 hours]</p>

## SECTION 11: Toxicological information

butanone	<p><b>Rabbit - Dermal - LD50</b> 6480 mg/kg</p> <p><b>Rat - Oral - LD50</b> 2737 mg/kg</p>
Reaction mass of ethylbenzene and xylene	<p><b>Rat - Oral - LD50</b> 3523 to 4000 mg/kg</p> <p><b>Rabbit - Dermal - LD50</b> 121236 mg/kg</p> <p><b>Rat - Inhalation - LC50 Vapour</b> 6350 to 6700 ppm [4 hours]</p>
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	<p><b>Rat - Male, Female - Oral - LD50</b> 3230 mg/kg OECD [Acute Oral toxicity - Acute Toxic Class Method]</p> <p><b>Rat - Male, Female - Dermal - LD50</b> &gt;3170 mg/kg OECD [Acute Dermal Toxicity]</p>
maleic anhydride	<p><b>Rat - Oral - LD50</b> 400 mg/kg</p> <p><b>Rabbit - Dermal - LD50</b> 2620 mg/kg</p>

**Conclusion/Summary [Product]** : Not available.

### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Mixture	N/A	37011.4	N/A	318.2	N/A
dimethyl ether	N/A	N/A	164000	309	N/A
n-butyl acetate	10768	N/A	N/A	21.1	N/A
butanone	2737	6480	N/A	N/A	N/A
Reaction mass of ethylbenzene and xylene	N/A	1100	N/A	11	N/A
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3230	N/A	N/A	N/A	N/A
maleic anhydride	400	2620	N/A	N/A	N/A

### Skin corrosion/irritation

#### Product/ingredient name

Methyl acetate

#### Result

**Rabbit - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

**Rabbit - Skin - Moderate irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

butanone

**Rabbit - Skin - Mild irritant**

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 14 mg

## SECTION 11: Toxicological information

### Rabbit - Skin - Mild irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 402 mg

### Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 500 mg

Fatty acids, C14-18 and C16-18-unsatd.,  
maleated

### Human - Skin - Moderate irritant

OECD 439

**Conclusion/Summary [Product]** : Not available.

### Serious eye damage/eye irritation

#### Product/ingredient name

methylethyl acetate

#### Result

### Rabbit - Eyes - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 100 mg

maleic anhydride

### Rabbit - Eyes - Severe irritant

Amount/concentration applied: 1 %

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

#### Product/ingredient name

Fatty acids, C14-18 and C16-18-unsatd.,  
maleated

#### Result

### Mouse - skin

OECD [Skin Sensitization: Local Lymph Node Assay]

Result: Sensitising

#### Skin

**Conclusion/Summary [Product]** : Not available.

#### Respiratory

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

## SECTION 11: Toxicological information

Not available.

**Conclusion/Summary [Product]** : Not available.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Result
Methyl acetate	STOT SE 3, H336 (Narcotic effects)
n-butyl acetate	STOT SE 3, H336 (Narcotic effects)
butanone	STOT SE 3, H336 (Narcotic effects)
2-methoxy-1-methylethyl acetate	STOT SE 3, H336 (Narcotic effects)
Reaction mass of ethylbenzene and xylene	STOT SE 3, H335 (Respiratory tract irritation)
	STOT SE 3, H336 (Narcotic effects)

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
Reaction mass of ethylbenzene and xylene	STOT RE 2, H373
maleic anhydride	STOT RE 1, H372 (respiratory system) (inhalation)

### Aspiration hazard

Product/ingredient name	Result
Reaction mass of ethylbenzene and xylene	ASPIRATION HAZARD - Category 1

### Information on likely routes of exposure

Not available.

### Potential acute health effects

<b>Eye contact</b>	: Causes serious eye irritation.
<b>Inhalation</b>	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
<b>Skin contact</b>	: Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
<b>Ingestion</b>	: Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Eye contact</b>	: Adverse symptoms may include the following: pain or irritation watering redness
<b>Inhalation</b>	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
<b>Skin contact</b>	: Adverse symptoms may include the following: irritation redness dryness cracking
<b>Ingestion</b>	: No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**SECTION 11: Toxicological information****Potential delayed effects** : Not available.**Long term exposure****Potential immediate effects** : Not available.**Potential delayed effects** : Not available.**Potential chronic health effects**

Not available.

**Conclusion/Summary [Product]** : Not available.**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.**Carcinogenicity** : No known significant effects or critical hazards.**Mutagenicity** : No known significant effects or critical hazards.**Reproductive toxicity** : No known significant effects or critical hazards.**Other information**

Not available.

**SECTION 12: Ecological information****12.1 Toxicity****Product/ingredient name**

Methyl acetate

**Result****Acute - LC50 - Fresh water**Fish - Fathead minnow - *Pimephales promelas*  
Age: 28 to 32 days; Size: 17.5 mm; Weight: 0.087 g  
320 mg/l [96 hours]  
Effect: Mortality

n-butyl acetate

**Acute - LC50 - Marine water**Fish - Inland silverside - *Menidia beryllina*  
185 ppm [96 hours]  
Effect: Mortality

butanone

**Acute - EC50 - Fresh water**Daphnia - Water flea - *Daphnia magna* - Larvae  
Age: <24 hours  
5091 mg/l [48 hours]  
Effect: Intoxication**Acute - LC50 - Fresh water**Fish - Fathead minnow - *Pimephales promelas*  
Age: 31 days; Size: 22 mm; Weight: 0.167 g  
3220 mg/l [96 hours]  
Effect: Mortality**Acute - EC50 - Marine water**Algae - Diatom - *Skeletonema costatum*  
>500 mg/l [96 hours]  
Effect: Population

Reaction mass of ethylbenzene and xylene

**Acute - LC50**OECD 203  
Fish - Trout - *Oncorhynchus mykiss*  
2.6 mg/l [96 hours]**Acute - LC50**OECD 202  
Daphnia - Daphnia - *Daphnia magna*  
1 mg/l [24 hours]

## SECTION 12: Ecological information

	<p><b>Acute - EC50</b>                      OECD 201                      Algae - Algae - <i>Selenastrum capricornutum</i>                      2.2 mg/l [73 hours]</p> <p><b>Chronic - NOEC</b>                      OECD 301F                      Micro-organism - Activated sludge - <i>Activated sludge</i>                      16 mg/l [28 days]</p>
<p>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3</p>	<p><b>Acute - LC50</b>                      OECD 203                      Fish                      2.8 mg/l [96 hours]</p> <p><b>Acute - EC50</b>                      Daphnia                      4 mg/l [48 hours]</p> <p><b>Acute - EC50</b>                      OECD 201                      Aquatic plants                      &gt;100 mg/l [72 hours]</p> <p><b>Acute - EC50</b>                      Micro-organism                      &gt;1000 mg/l [3 hours]</p> <p><b>Chronic - NOEC</b>                      OECD 202                      Daphnia                      0.78 mg/l [21 days]</p>
<p>Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate</p>	<p><b>Acute - LC50</b>                      OECD 203, semistatic                      Fish - <i>Brachydanio rerio</i>                      0.9 mg/l [96 hours]</p> <p><b>Chronic - NOEC - Fresh water</b>                      OECD [Daphnia Magna Reproduction Test]                      Daphnia                      1 mg/l [21 days]</p> <p><b>Acute - EC50 - Fresh water</b>                      OECD [Alga, Growth Inhibition Test]                      Algae                      1.68 mg/l [72 hours]</p>
<p>maleic anhydride</p>	<p><b>Acute - LC50 - Fresh water</b>                      Fish - Western mosquitofish - <i>Gambusia affinis</i> - Adult                      230 ppm [96 hours]  <u>Effect:</u> Mortality</p>

**Conclusion/Summary [Product]** : Not available.

### 12.2 Persistence and degradability

Not available.

**Conclusion/Summary [Product]** : Not available.

**SECTION 12: Ecological information****12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
dimethyl ether	0.07	-	Low
methyl acetate	0.18	-	Low
n-butyl acetate	2.3	-	Low
butanone	0.3	-	Low
Reaction mass of ethylbenzene and xylene	3.16	-	Low
maleic anhydride	-2.78	-	Low

**12.4 Mobility in soil**

**Soil/water partition coefficient** : Not available.

**Mobility** : Not available.

**12.5 Results of PBT and vPvB assessment**

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
dimethyl ether	No	N/A	N/A	No	N/A	N/A	N/A
methyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
n-butyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
butanone	No	N/A	N/A	No	N/A	N/A	N/A
2-methoxy-1-methylethyl acetate	No	N/A	N/A	No	N/A	N/A	N/A
Reaction mass of ethylbenzene and xylene	N/A	N/A	N/A	Yes	N/A	N/A	N/A
Fatty acids, C14-18 and C16-18-unsatd., maleated	No	N/A	N/A	No	N/A	N/A	N/A
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl- $\omega$ -hydroxypoly (oxyethylene) and $\alpha$ -3	No	N/A	N/A	No	N/A	N/A	N/A
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl	N/A	N/A	N/A	Yes	N/A	N/A	N/A
1,2,2,6,6-pentamethyl-4-piperidyl sebacate	N/A	N/A	N/A	Yes	N/A	N/A	N/A
maleic anhydride	N/A	N/A	N/A	Yes	N/A	N/A	N/A

**12.6 Other adverse effects** : No known significant effects or critical hazards.

**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**13.1 Waste treatment methods****Product**

## SECTION 13: Disposal considerations

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.





### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue
	15 01 10* packaging containing residues of or contaminated by hazardous substances

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1950	UN1950	UN1950	UN1950
14.2 UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3 Transport hazard class(es)	2 	2 	2.1 	2.1 
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

### Additional information

**ADR/RID** : **Tunnel code** (D)

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

### UK (GB)/REACH

#### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

E-COAT REPAIR 12 WHITE AEROSOL

## SECTION 15: Regulatory information

None of the components are listed.

### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
☑ mixture	≥90	3

**Labelling** : Not applicable.

### Seveso Directive

This product is controlled under the Seveso Directive.

### Danger criteria

Category
☑ 3a

### National regulations

Product/ingredient name	List name	Name on list	Classification	Notes

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

☑ Indicates information that has changed from previously issued version.

### **Abbreviations and acronyms**

: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ATE = Acute Toxicity Estimate  
 GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = GB CLP-specific Hazard statement  
 IATA = International Air Transport Association  
 IMDG = International Maritime Dangerous Goods  
 IMO = International Maritime Organization  
 N/A = Not available  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
 RRN = REACH Registration Number  
 SGG = Segregation Group  
 vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification

E-COAT REPAIR 12 WHITE AEROSOL

## SECTION 16: Other information

Classification	Justification
Aerosol 1, H222, H229 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H336	On basis of test data Calculation method Calculation method Calculation method

### Full text of abbreviated H statements

H220	Extremely flammable gas.
H222, H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

### Full text of classifications

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aerosol 1	AEROSOLS - Category 1
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Gas 1A	FLAMMABLE GASES - Category 1A
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Press. Gas (Comp.)	GASES UNDER PRESSURE - Compressed gas
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of revision : 2/19/2026

Version : 1.01

## SECTION 16: Other information

Date of previous issue : 3/5/2025

### Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2026 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.